يترو فرهان كستر جنوب

Q Tehran, Tehransar

Elcometer 135B Bresle Patch



Elcometer 135B Bresle Patch

Supplied with the Elcometer 138 Bresle Salt Kit, the Elcometer 135B is a self-adhesive rubber film patch with a sealed compartment used for taking samples of soluble impurities on a test surface.

Each pack contains 25 Bresle Patches.

Surface Cleanliness
Surface contamination from
salts such as chlorides,
sulphates and nitrates have
been shown to lead to
blistering of organic coatings,
particularly in immersion
conditions.

Measuring the surface cleanliness of the substrate alone prior to a coating being applied may not be sufficient. If more than one layer of coating is being used, it is necessary to monitor and record the cleanliness of each layer prior to applying the next coating. When using amine cured epoxy coatings, for example, in low ambient temperatures or in high humidity, a surface oiliness or exudate may cause intercoating adhesion failure.

TECHNICAL SPECIFICATION		
Size	5.2 cm x 5.2 cm (2.0" x 2.0")	
Test Area	12.5 cm² (1.93 sq. inches)	Î
Sample Volume	2.6 ml ±0.6 ml	
Tests per Kit	25	
Part Number	E135-B Elcometer 135B Bresle Patch, Box of 25	- 6

Related Products



Elcometer 138 Bresle Salt Kit

Elcometer 138 Bresle Salt Kit:

Supplied with Elcometer 135B Bresle Patches and the Elcometer 138 Conductivity Meter, this kit provides all the equipment required to measure the level of salt contamination on a surface, prior to coating.



Elcometer 138/2 Surface Contamination Kit

Elcometer 138/2 Surface Contamination Kit:

Supplied with Elcometer 135A Bresle Samplers and various test strips, this kit provides a low cost, simple method of measuring the salt, pH, chloride and iron (ferrous ion) concentration on a test surface in accordance with ISO 8502-6.

data sheet



Elcometer 134A Chloride Ion Test Kit for Abrasives



Elcometer 134A Chloride Ion Test Kit for Abrasives:

Chlorides deposited on a surface by contaminated abrasives during blasting can cause a coating to fail prematurely. Using the Elcometer 134A in the field will accurately identify contamination and prevent costly surface-related failures.

Elcometer 134W Chloride Ion Test Kit for Water:

Used to monitor recycled water (after it has been applied) to establish the effectiveness of salt removal, this test is ideal when mixing concrete and when washing steel.

elcometer

ENGLAND

Elcometer Limited Edge Lane Manchester M43 6BU

Tel: +44 (0)161 371 6000 Fax: +44 (0)161 371 6010 e-mail: sales@elcometer.com www.elcometer.com

USA

Elcometer Inc. 1893 Rochester Industrial Drive Rochester Hills Michigan 48309

Tel: +1 248 650 0500 Toll Free: 800 521 0635 Fax: +1 248 650 0501 e-mail: inc@elcometer.com www.elcometer.com

ASIA & THE FAR EAST

Elcometer (Asia) Pte Ltd 896 Dunearn Rd Sime Darby Centre #3-09 Singapore 589472, Republic of Singapore

Tel: +65 6462 2822 Fax: +65 6462 2860 e-mail: asia@elcometer.com www.elcometer.com

Elcometer 134W Chloride Ion Test Kit for Water



Elcometer 134S Chloride Ion Test Kit for Surfaces



Elcometer 134 CSN Chloride, Sulphate & Nitrate Kit

Elcometer 134S Chloride Ion Test Kit for Surfaces:

Chloride salts left on the surface before the first coat is applied can result in the coating system being forced off the surface by corrosion or blistering before the full life of the coating has been reached. ensure that the chloride has been removed, it is essential that the surface is tested before the coating is applied.

Elcometer 134 CSN Chloride, Sulphate & Nitrate Kit:

Designed to accurately measure surface chloride, sulphate and nitrate ions in minutes, the Elcometer 134 CSN Salt Kit offers a single kit solution for testing in the field.

BELGIUM

Elcometer SA Rue Vallée 13 B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10 Fax: +32 (0)4 374 06 03 e-mail: be_info@elcometer.be www.elcometer.be

NETHERLANDS

Elcometer NL Newtonlaan 115 3584 BH Utrecht

Tel: +31 (0)30 210 7005 Fax: +31 (0)30 210 6666 e-mail: nl info@elcometer.com www.elcometer.com

FRANCE

Elcometer Sarl 97 Route de Chécy 45430 BOU

Tel: +33 (0)2 38 86 33 44 Fax: +33 (0)2 38 91 37 66 e-mail: fr_info@elcometer.fr www.elcometer.fr

GERMANY

Elcometer Instruments GmbH Ulmer Strasse 68 D-73431 Aalen

Tel: +49 (0)7361 52806 0 Fax: +49 (0)7361 52806 77 e-mail: de_info@elcometer.de www.elcometer.de

يتروفرهان كستر جنوب

FGJ-NDT.IR DIGINDT.IR