



## LM570/LM585 SERIES **NEW**

### Laser Levelers

These laser levelers are equipped with green LD laser, suitable for large or bright work places.

Its applications include: horizontal, vertical, cross line projection for decoration, building construction, home decoration, renovation, furniture installation, flooring, and project layout.

- Osram LD green laser(LM576/585LD)
- Self-leveling mode & manual mode
- Outdoor pulse mode
- 5200mAh Li-ion battery
- Type-C DC-in port
- Complimentary bracket



● LM576LD



● LM312 wall mount  
LM312 is suitable for  
LM573LD-II/575LD/576LD only.

	LM570LD-II	LM573LD-II	LM575LD	LM576LD	LM585LD
Certificates (LM570LD-II/575LD only)	CE, RoHS				
Laser type	Green LD	Green LD	Green LD	Osram green LD	Osram green LD
Laser lines	2 lines	3D 12 lines	3D 12 lines	3D 16 lines	8 lines
Operating distance	10m	40m	40m	30m	30m
Laser accuracy	±3mm/10m	±3mm/10m	±3mm/10m	±3mm/10m	±3mm/10m
Outdoor pulse mode		√	√	√	√
Remote control		√	√	√	√
Self-leveling range	3°±1°	±3°	±3°	±3°	±3°
Self-leveling time	3s	<3s	<3s	<3s	<3s
Working hours	4h	>6h	>6h	>4h	>4h
Laser wavelength	520nm				
Laser class	2				
Power	LM570LD-II: 1.5V battery x 2 (LR6); LM573LD-II/LM575LD/LM576LD/LM585LD: 3.7V Li-ion battery 5200mAh				
Product net weight	LM570LD-II: 240g; LM573LD-II/LM575LD: 694g; LM576LD: 653g; LM585LD: 591g				
Product size	LM570LD-II: 85.5mm x 62mm x 90.3mm; LM573LD-II: 119mm x 89mm x 138mm; LM575LD/LM576LD: 138mm x 89mm x 147mm; LM585LD: 138mm x 89mm x 136mm				
Standard accessories	USB cable, adapter, English manual				
Standard individual packing	Gift box, tool box				
Standard quantity per carton	LM570LD-II: 20pcs; LM573LD-II/LM575LD/LM576LD/LM585LD: 4pcs				
Standard carton measurement	LM570LD-II: 420mm x 320mm x 350mm; LM573LD-II/LM575LD/LM576LD/LM585LD: 620mm x 355mm x 325mm				
Standard carton gross weight	LM570LD-II: 10.71kg; LM573LD-II/LM575LD/LM576LD: 10.63kg; LM585LD: 10.22kg				

+982165565901

+982144584619

+989034119385

پتروفهان گستر جنوب

FGJ-NDT . IR

DIGINDT . IR