

## Light intensity measuring instrument

testo 540 - Pocket-sized Lux meter

- Sensor adjusted to spectral sensitivity of the human eye
- Hold-function and max./min. values
- Display illumination
- Lux and Foot Candle settings



testo 540



## Technical data / Accessories

### testo 540

testo 540 pocket sized Lux meter incl. protection cap, batteries and factory calibration document

Part no. 0560 0540



Sensor type	Silicone photodiode
Measuring range	0 to 99,999 Lux / 0 to 9,920 FtC
Accuracy ±1 digit	±3 Lux or ±3 % of m.v. (compared to reference Class B, DIN 5032 Part 7)
Resolution	1 Lux (0 to 19,999 Lux) / 10 Lux (remaining range) 0.1 FtC (0 to 1,860 FtC) / 1 FtC (remaining range)

#### General technical data

Measurement rate	0.5 s
Storage temperature	-40 to +70 °C
Protection class	IP40
Operating temperature	0 to +50 °C
Battery type	2 AAA batteries
Battery life	200 h (average, without display illumination)
Dimensions	133 x 46 x 25 mm
Weight	95 g (incl. batteries and protective cap)
Warranty	2 years

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR  
DIGINDT.IR