

LI-ION RECHARGEABLE

XPR-5582RX
XPR-5582GX

INTEGRITAS™ INTRINSICALLY SAFE LANTERN

NIGHTSTICK®

Life Depends on Light™

1750

POWERFUL LUMENS

INCLUDING HIGH & LOW



Rear green safety lights provide visibility in smoke filled applications



Carry strap with seat belt style buckle for additional hands-free use



Convenient locking snap-in charger included




Dustproof/Waterproof (IP-67) and chemical/heat resistant for any environment



AVAILABLE IN MULTIPLE COLORS

FL 1 STANDARD	HIGH	LOW
	1750 LUMENS	600 LUMENS
	5h	11h
	552m	325m
	81250cd	27083cd



1750 LUMENS



INTRINSICALLY SAFE

PRODUCT SPECIFICATION SHEET

INTEGRITAS™

LANTERN

LI-ION RECHARGEABLE

ITEM NUMBER/UPC

XPR-5582RX (Red), UPC# 0 17398 806824
XPR-5582GX (Green), UPC# 0 17398 807029

MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

CERTIFICATIONS

- cETLus, CE, Meets requirements of NFPA-1971-8.6 (2013), Charger meets requirements of NFPA-1901 (2009) Mounted in any Position
- US Patent 9,713,217

CASE MATERIAL

- Glass filled nylon polymer

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 1750L, 5 hrs. runtime
- LOW: 600L, 11 hrs. runtime

CANDELA

FLASHLIGHT

- HIGH: 81,250
- LOW: 27,083

BEAM DISTANCE

FLASHLIGHT

- HIGH: 552m
- LOW: 325m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 7.54 in / 19.2 cm
- WIDTH: 4.26 in / 10.8 cm
- DEPTH: 5.83 in / 14.8 cm
- WEIGHT: 2 lbs. 11 oz. / 1219 g

BATTERY

- Rechargeable Li-ion battery pack

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Lantern
- Li-ion rechargeable battery pack
- Locking snap-in charger (5582-CHGR1)
- AC power supply
- DC direct wire kit with in-line fuse
- Removable shoulder strap
- Instruction manual

FL 1 STANDARD	HIGH	LOW
	1750 LUMENS	600 LUMENS
	5h	11h
	552m	325m
	81250cd	27083cd
	2m	
	1m	



Bayco Products, Inc. XPR-5582
640 S. Sanden Blvd., Wylie, TX 75098

ID 4003544
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CLASS I DIV 2 GRPS A-D T3
CLASS II & III DIV 2 GRPS F-G T135°C
CLASS I ZONE 2 Group IIC T3
-20°C ≤ Tamb ≤ +40°C
3.7V/Cell 5582-BATT



WARNING: Risk of ignition - Do not open in a hazardous area.
AVERTISSEMENT: Ne pas ouvrir dans une zone dangereuse.
WARNING: Risk of ignition - Do not charge batteries in a hazardous area.
AVERTISSEMENT: Danger d'inflammation - Ne pas charger les piles dans une zone dangereuse.

CERTIFIED



AVAILABLE IN MULTIPLE COLORS