

پترو فرهان گستر جنوب

Tehran, Tehransar

94 dB/125 Hz

SOUND CALIBRATOR

Model : SC-943

ISO-9001, CE, IEC1010



Lutron



LUTRON ELECTRONIC

The Art of Measurement

94 dB/125 Hz

SOUND CALIBRATOR

Model : SC-943

FEATURES

| |
|---|
| Standard 94 dB/125 Hz |
| Sound calibrator, useful to calibrate another " |
| Sound Level Meter " precisely. |

General/ Electrical Specification (23 ±5°C)

| | |
|--|--|
| Frequency | 125 Hz ±2% |
| Sound Pressure Level (at 23 ±5°C) | 94 dB ±0.75 dB. * Spec. tested under the environment RF Field Strength less than 3 V/M & frequency less than the 30 MHz only. |
| Suitable Microphone Type | 1 " mic. & 0.5 " mic. * 0.5" microphone is calibrated with 0.5" mic. adapter(standard acc.) |
| Distortion | 94 dB range harmonic distortion : 3 %. |
| Operating Temp. | 0 °C to 50 °C (32 °F to 122 °F). |
| Power Supply | DC 9 V battery (006P, 6F22) x 2 PCs. * Recommend use the Alkaline or Heavy duty type battery. |
| Power Consump. | Approx. DC 10.6 mA (in BAT.TEST position) Approx. DC 2.3 mA (in ON position) |
| Battery Check | Build in " Low Battery Indicator " |
| Dimension | Dia 50 mm (round) x 145 mm (length). |
| Weight | Approx. 277 g/0.61 LB (meter only). |
| Accessories Included | Instruction manual..... 1 PC. 0.5" mic. adapter..... 1 PC. Adjust Screw Driver..... 1 PC. Carrying case, CA-03..... 1 PC. |

+982165565901

+982144584619

+989034119385

پتروفهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR