

ACC., Velocity, Displacement VIBRATION METER

Model : VB-8220



ISO-9001, CE, IEC1010

Tehran, Tehransar



FEATURES

- * Separate professional vibration sensor.
- * Acceleration : 200 m/s².
- * Velocity : 200 mm/s.
- * Displacement (p-p) : 2 mm.
- * RMS, Peak value.
- * RS-232 computer interface.
- * DC 9V battery (006P).



LUTRON ELECTRONIC

The Art of Measurement

+982165565901

+982144584619

+989034119385

پتروفهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR

VIBRATION METER

Model : VB-8220

FEATURES

- * Applications for industrial vibration monitoring :
All industrial machinery vibrates. The level of vibration is a useful guide to machine condition. Poor balance, misalignment & looseness of the structure will cause the vibration level increase, it is a sure sign that the maintenance is needed.
- * Frequency range 10 Hz - 1 kHz, sensitivity relative meet ISO 2954.
- * Professional vibration meter supply with vibration sensor and magnetic base, full set.
- * Velocity measuring range : 200 mm/s.
- * Acceleration measuring range : 200 m/s²
- * Displacement measuring range : 2 mm (p-p).
- * RMS & Peak measurement.
- * Wide frequency range.
- * Data hold button to freeze the desired reading.
- * Memory function to record maximum and minimum reading with recall.
- * Separate vibration probe, easy operation
- * RS 232 computer interface.
- * Optional data acquisition software for data record & datalogger.
- * Super large LCD display.
- * Microcomputer circuit, high performance.
- * Auto shut off saves battery life.
- * Built-in low battery indicator.
- * Heavy duty & compact housing case.
- * Complete set with the hard carrying case.

SPECIFICATIONS

Display	61 mm x 34 mm super large LCD display. 15 mm (0.6") digit size.
Measurement	Velocity, Acceleration, Displacement, RMS value, Peak value, Data hold, Max. & Min. value.
Range	<i>Velocity :</i> 200 mm/s : 0.5 to 199.9 mm/s
	<i>Acceleration :</i> 200 m/s ² : 0.5 to 199.9 m/s ²
	<i>Displacement (p-p) :</i> 2 mm : 0.005 to 1.999 mm * p-p : Peak to Peak

Tehran, Tehransar



Frequency range	10 Hz to 1 KHz * Sensitivity relative during the the frequency range meet ISO 2954.	
Accuracy	± (5 % + 2 d) reading , 160 Hz, 80 Hz. * 23 ± 5 °C	
Calibration point	Velocity	50 mm/s (160 Hz)
	Acceleration	50 m/s^2 (160 Hz)
	Displacement (p-p)	0.05 mm (160 Hz)
Circuit	Exclusive microcomputer circuit.	
Data hold	Freeze the desired reading.	
Peak measurement	To measure the peak value.	
Memory	Maximum & Minimum value.	
Power off	Auto shut off, saves battery life, or manual off by push button.	
Sampling time	Approx. 1 second.	
Data output	RS 232 serial output.	
Operating temperature	0 to 50 °C (32 to 122 °F).	
Operating humidity	Less than 80% RH.	
Power supply	Alkaline or heavy duty type, DC 9V battery, 006P, MN1604 (PP3) or equivalent.	
Power consumption	Approx. DC 8 mA.	
Weight	Meter	230 g/0.50 LB
	Probe with magnetic base	110 g/0.24 LB
Dimension	Meter : 180 x 72 x 32 mm (7.1 x 2.8 x1.3 inch). Vibration sensor probe: Round 18 mm Dia. x 40 mm.	
Accessories included	Instruction manual..... 1 PC. Vibration sensor (VB-82)..... 1 PC. Cable..... 1 PC. Magnetic base..... 1 PC. Carrying Case..... 1 PC.	
Optional accessories	* Software (Windows version, data record & data acquisition)SW-U801-WIN * RS232 cable..... UPCB-01 * USB cable..... USB-01	

* Appearance and specifications listed in this brochure are subject to change without notice.

0601-VB8220

☎ +982165565901

☎ +982144584619

☎ +989034119385

بنیروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR