

Ultrasonic Thickness Gauge WT-130A

Specification:

Measuring range	1.00 ~ 300.0mm
Data storage	1500
Probe selection	√
Operation frequency	5MHz/2.5MHz
Measurement error	±(0.5%H+0.05)mm
Resolution	0.01mm(1.00 to 99.99mm) 0.1mm(100 to 300mm)
Lower limit of pipe measurement	Φ20x3mm (steel)
Adjustment range of sound speed	1000 ~ 9999m/s
Temperature range of operation	0 ~ 40°C
Battery	3 Ni-MH rechargeable batteries of 1.2V
USB charging	5V 1A
Dimensions	65x146x30mm
Weight	130G



Features:

- ✓ Measuring the thickness and the sound speed of various materials.
- ✓ High contrast 2.4" color-screen HD display with backlit & 5 selectable color display
- ✓ Auto calibration
- ✓ Units: mm/inch
- ✓ Storage data (up to 500 data) and recall function
- ✓ Statistic view (Min/Max/Avg/High/Low)
- ✓ Automatic shutdown
- ✓ Built in metal calibration block

Package List:

- 1 x Main device
- 1 x Transducer (probe)
- 3 x Rechargeable batteries (1.2V per)
- 1 x USB cable
- 1 x Charger (5V, 1A)
- 1 x Hard Carrying case
- 1 x English User Manual

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR