

TES-1500 Capacitance Meter



FEATURES

- 0.5% Accuracy.
- Overload Fuse protection.
- Test Clips/Direct insert jack for easy measurement.



SPECIFICATION

Range	Resolution	Accuracy	Max. In-range Display	Test Frequency	Overload Protection
200pF	0.1pF	+/- (0.5%+1+0.5pF)	199.9pF	800Hz	0.25A/250 Fuse Protection
2nF	1pF	+/- (0.5%+1)	1.999nF	800Hz	0.25A/250 Fuse Protection
20nF	10pF	+/- (0.5%+1)	19.99nF	800Hz	0.25A/250 Fuse Protection
200nF	100pF	+/- (0.5%+1)	199.9nF	800Hz	0.25A/250 Fuse Protection
2 m F	1nF	+/- (0.5%+1)	1.999 m F	800Hz	0.25A/250 Fuse Protection
20 m F	10nF	+/- (0.5%+1)	19.99 m F	80Hz	0.25A/250 Fuse Protection
200 m F	100nF	+/- (0.5%+1)	199.9 m F	8Hz	0.25A/250 Fuse Protection
2000 m F	1 m F	+/- (1%+1)	1999 m F	8Hz	0.25A/250 Fuse Protection
20mF (20000 m F)	10 m F	+/- (2%+1)	19.99mF	8Hz	0.25A/250 Fuse Protection

Operating Principle	Dual Slop Integration
Display Rate	Approx. 2 times per second
Zero Adjustment	+ - 20pF Approx.
Operating/Storage Condition	0°C to 40°C < 80% R.H. -10°C to 60°C < 70% R.H.
Power Source	006P DC 9V 1pc
Size & Weigh	135mm(L) x 72mm(W) x 33mm(H) & 207g
Accessories	Test Clips, Spare Fuse, Battery & Instruction Manual

10-12F 10-9F 10-6F

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR