

پتروفرهان گستر جنوب

Tehran, Tehransar



پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR

+982165565901

+982144584619

+989034119385

Specifications		MS8340A	MS8340B
Specifications	Range	Accuracy	
DC Voltage	600mV	$\pm[0.5\%+3]$	
	6V/60V/600V/1000V	$\pm[0.8\%+3]$	
	220mV		$\pm[0.05\%+3]$
	2.2V/22V/220V/1000V		$\pm[0.1\%+3]$
AC Voltage	6V/60V/750V(50Hz)	$\pm[1.0\%+4]$	
	6V/60V/750V(2kHz)	$\pm[2.0\%+3]$	
	220mV/2.2V/22V/220V/700V(50Hz)		$\pm[0.8\%+4]$
	220mV/2.2V/22V/220V/700V(2kHz)		$\pm[2.5\%+3]$
DC Current	600uA/6mA/60mA/600mA/10A	$\pm[1.2\%+4]$	
	220uA/2200uA/22mA/220mA/10A		$\pm[1.0\%+4]$
AC Current	600uA/6mA/60mA/600mA	$\pm[1.5\%+3]$	
	10A	$\pm[2.0\%+3]$	
	220uA/2200uA/22mA		$\pm[1.5\%+3]$
Resistance	220mA/10A		$\pm[1.8\%+3]$
	600Q/6KQ/60KQ/600KQ/6MQ/60MQ	$\pm[1\%+2]$	
	220Q/2.2KQ/22KQ/220KQ		$\pm[0.8\%+2]$
Capacitance	2.2MQ/22MQ/220MQ		$\pm[1.0\%+2]$
	40nF/400nF	$\pm[3.0\%+2]$	
	40n4uF/40uF/400uF	$\pm[3.5\%+2]$	
Frequency	22nF/220nF/2.2uF/22uF/220uF/2.2mF/22mF/220mF		$\pm[2.5\%+3]$
	0~10MHz	$\pm[0.2\%+3]$	
	0~220MHz		$\pm[0.2\%+3]$
Duty Cycle	5%~95%	$\pm 1\%$	$\pm 1\%$
Temperature	-10°C~700°C	$\pm[2\%+2]$	
	14°F~1292°F	$\pm[2\%+4]$	
Special Functions			
LCD Display	counts	6000	22000
Auto Ranging	Auto & manual	●	●
APD	Auto Power Off	●	●
REL	Relative Measurement	●	●
PEAK	Peak Measurement		●
LPF	1KHz Low Pass Filter	●	
Diode	2.7V	●	●
Continuity Buzzer	<50Q	●	●
MAX/MIN		●	●
Data Hold		●	●
True RMS			●
Display Backlight		●	●
LBD	Low Battery Display	●	●
USB Interface	Windows OS		●
General			
Power Supply	4x1.5V AA Batteries		
Product Size	205mmx102mmx58mm/8.1"x4.0"x2.2"		
Product Weight	390g/0.86lb		
Safety Rating	CE GS CAT. III 1000V		