

LCD display

3 PHASE ROTATION TESTER

Model : RT-616

ISO-9001, CE, IEC1010

FGJ-NDT .IR

DIGINDT .IR

پتروفرهان گستر جنوب

Tehran, Tehransar



+982165565901

+982144584619

+989034119385



Lutron

LUTRON ELECTRONIC

The Art of Measurement

FGJ-NDT.IR
DIGINDT.IR

LCD display
3 PHASE ROTATION TESTER
Model : RT-616



پتروفرهان گستر جنوب

FEATURES


- * Electronic (not mechanical) rotation test, high reliability.
- * LCD display, easy ready and simple operation.
- * Signal input voltage : 100V AC up to 660V AC max.

+982165565901
+982144584619
+989034119385


GENERAL SPECIFICATIONS

Signal Input	100V AC up to 660 AC maximum, Voltage	3 min. limit for over 500V AC.
Signal Current	Approx. 7 mA per phase.	
Consumption		
Signal Freq.	45 to 70 Hz.	
Range		
Circuit	* Electronic (not mechanical). * Custom one-chip of microprocessor LSI circuit.	
Power Supply	DC 9V battery. 006P, MN1604 (PP3) or equivalent. Approx.	
Power	Approx. DC 8 mA.	
Consumption		
Operating Temperature	0 to 50 °C (32 to 122 °F).	
Operating Humidity	Less than 80% RH.	
Dimension	100 x 50 x 25 mm. 3.9 x 1.9 x 1.0 inch.	
Weight	150 g/0.33 lb.	
Standard	* Operational manual.....1 PC	
Accessories	* Meter with 3 PCs 40 cm length test lead and banana Plug.....1 SET * Alligator clip.....3 PC	

Clockwise (correct)




Counter clockwise (correct)




Line is no connection (Incorrect)

L1 missing



L2 missing



L3 missing



L1, L2, L3 missing



Tehran, Tehransar

* Appearance and specifications listed in this brochure are subject to change without notice.