

**1500 g x 0.05 g**  
**DIGITAL BALANCE**

**Model : GM-1500P**

**ISO-9001, CE, IEC1010**

پتروفهان گستر جنوب

**FGJ-NDT.IR**

**DIGINDT.IR**

Tehran, Tehransar



+982165565901

+982144584619

+989034119385



**Lutron**


**LUTRON ELECTRONIC**

**The Art of Measurement**

# DIGITAL BALANCE, 1500 g x 0.05 g

Model : GM-1500P

Tehran, Tehransar



## FEATURES

- \* Microprocessor circuit with high accuracy & better performance.
- \* High resolution & wide measuring capacity, 1500 g x 0.05 g, 50 oz x 0.002 oz.
- \* Large LCD display, 18 mm ( 0.7" ) digit size, easy read out.
- \* Built-in gram & oz display unit, select by the internal slide switch.
- \* Built-in self calibration system, the calibration value can memorize into EEPROM circuit permanently even power off.
- \* Counting scale function.
- \* RS232 computer interface.
- \* Accept battery or AC/DC adapter power source, two way power supply.
- \* Heavy duty ABS housing plastic case.

## SPECIFICATIONS

Display	LCD, 18 mm ( 0.7" ) digit size, 5 digits with annunciator.		
Function	Weighting & counting.		
Weighting range & resolution	Unit	Range	Resolution
	g	0.50 g to 1500 g	0.05 g
	oz	0.02 oz to 49.998 oz 50 oz to 52.8 oz	0.002 oz 0.005 oz
Min. display weight	g	0.50 g	
	oz	0.03 oz	
Unit select	g or oz, select by internal slide switch.		
Accuracy	± ( 0.05 % + 0.2g ) * Within two hours after self calibration be executed at 23 ± 5°C		
Sampling time	Approx. 1 second.		
Tare control	Approx. 1500 g max.		
Transducer	Load cell.		
Circuit	Microprocessor circuit.		
Auto self calibration	Use 500 g or 1000 g standard weight to execute self-calibration automatically.		
Counting sample no.	10 PCs, 20 PCs, 50 PCs or 100 PCs.		
Operating temperature	0 to 50 °C ( 32 to 122 °F ).		
Operating humidity	Less than 80% RH.		
Size	Cabinet	250 x 188 x 70 mm.	
	Platform	185 x 185 mm.	
Power Supply	6 x 1.5V AA (UM-3) battery x 6 PCs, or DC 9V adapter ( optional ).		
Power Consumption	Approx. DC 25 mA.		
Accessory Included	Operation Manual.....1 PC.		
Optional Accessories	* Software ( Windows version ), SW-U801-WIN. * RS232 cable, UPCB-01. * USB cable, USB-01.		

بتروفرهان گستر جنوب

**FGJ-NDT.IR**  
**DIGINDT.IR**

+982165565901  
+982144584619  
+989034119385

\* Appearance and specifications listed in this brochure are subject to change without notice.

0902-GM1500P