

**600 g x 0.02 g**  
**DIGITAL BALANCE**  
**Model : GM-600P**

Tehran, Tehransar



**ISO-9001, CE, IEC1010**



بتروفرهان گستر جنوب

**FGJ-NDT.IR**

**DIGINDT.IR**

## FEATURES



- \* Microprocessor circuit with high accuracy & better performance.
- \* 0.02 g & 0.001 oz resolution & wide measuring capacity.
- \* Large LCD display, 18 mm ( 0.7" ) digit size, easy read out.
- \* Built-in gram & oz display unit, select by the internal slide switch.
- \* Built-in self calibration system, the calibration value can memorize into EEPROM circuit permanently even power off.
- \* High precision counting scale function.
- \* RS-232 computer interface.
- \* Accept battery or AC/DC adapter power source, two way power supply.
- \* Built-in " level bubble " & the adjustable " rubber pads " .
- \* Heavy duty ABS housing plastic case.

+982165565901

+982144584619

+989034119385

**Lutron**

**LUTRON ELECTRONIC**

***The Art of Measurement***

600.0 g x 0.02 g

# DIGITAL BALANCE

Model : GM-600P



## FEATURES

* Microprocessor circuit with high accuracy & better performance.	
* 0.02 g & 0.001 oz resolution & wide measuring capacity.	
* Large LCD display, 18 mm ( 0.7" ) digit size, easy read out.	پروفهان گستر جنوب
* Built-in gram & oz display unit, select by the internal slide switch.	FGJ-NDT.IR DIGINDT.IR
* Built-in self calibration system, the calibration value can memorize into EEPROM circuit permanently even power off.	
* High precision counting scale function.	
* RS-232 computer interface.	
* Accept battery or AC/DC adapter power source, two way power supply.	
* Built-in " level bubble " & the adjustable " rubber pads ".	
* Heavy duty ABS housing plastic case.	

## SPECIFICATIONS

Display	LCD, 18 mm ( 0.7" ) digit size, 5 digits with annunciator.		
Measuring range & Resolution	<i>Unit</i>	<i>Range</i>	<i>Resolution</i>
	g	0.20 g to 600 g	0.02 g.
Min. Display Weight	oz	0.007 oz to 21.164 oz	0.001 oz
	g	0.20 g	
Unit Select	oz	0.007 oz	
Accuracy	g or oz, select by internal slide switch. ± ( 0.05 % + 0.08 g ) * Within two hours after self calibration be executed. * 23 ± 5 °C		
Sampling time	Approx. 1 second.		
Tare Control	Approx. 600 g max.		
Transducer	Load cell.		
Circuit	Microprocessor circuit.		
Auto Calibration	Use 200 g or 400 g standard weight to execute self-calibration automatically.		
Operating Temperature	0 to 50 °C ( 32 to 122 °F ).		
Operating Humidity	Less than 80% RH.		
Size	Cabinet	250 x 180 x 70 mm	
	Platform	Round, 120 mm Dia.	
Power Supply	6 x 1.5V AA (UM-3) battery x 6 PCs, or DC 9V adapter, optional.		
Power Consumption	Approx. DC 25 mA.		
Accessory Included	Operation Manual.....1 PC.		+982165565901
Optional accessories	* Software ( Windows version ),		+982144584619
	SW-U101-WIN or SW-U801-WIN		+989034119385
	* RS232 cable, UPCB-01		
	* 200 g calibration weight, WT-200		

\* Appearance and specifications listed in this brochure are subject to change without notice. 0403-GM600P