

Pocket

UV LIGHT METER

Model : UV-340A



ISO-9001, CE, IEC1010

Tehran, Tehransar



Lutron

LUTRON ELECTRONIC

The Art of Measurement

+982165565901

+982144584619

+989034119385

پتروفهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR

UV LIGHT METER

Model : UV-340A



Tehran, Tehransar

FEATURES

- * Professional, high quality UV meter.
- * Ultra-violet irradiation measurement for UVA & UVB.
- * UV detector spectrum from 290 nm to 390 nm.
- * Hi, Lo measurement range. 19990 and 1999 $\mu\text{W}/\text{cm}^2$.
- * Exclusive UV sensor structure.
- * Sensor with cosine correction filter.
- * Build Zero button.
- * Microprocessor circuit provides high reliability and durability.
- * Separate UV LIGHT probe allows user to measure the UV light at an optimum position.
- * LCD display, easy readout.
- * Heavy duty & compact housing case.

APPLICATIONS

Industrial

- * Monitoring blue light radiation hazards in welding.
- * UV sterilization
- * Graphic arts.
- * Photochemical matching.
- * UV EPROM erasure.
- * Photoresist exposure.
- * Curing of inks, adhesives and coatings.

Laboratory

- * Weathering " degradation studies."
- * UV sterilization
- * Virology.
- * Microbial genetics.
- * DNA research. * Biologic hoods.
- * General laboratory use.

SPECIFICATIONS

Display	LCD size : 18 mm x 45 mm. Maximum indication 1999.
Measurement ranges & resolution	2 ranges : Hi & Lo range Lo range : 1999 $\mu\text{W}/\text{cm}^2 \times 1 \mu\text{W}/\text{cm}^2$ Hi range : 19990 $\mu\text{W}/\text{cm}^2 \times 10 \mu\text{W}/\text{cm}^2$ * 1000 $\mu\text{W}/\text{cm}^2 = 1 \text{mW}/\text{cm}^2$
UV sensor spectrum	Band pass 290 nm to 390 nm.
Accuracy	$\pm (4\% \text{ FS} + 2 \text{ dgt})$ FS : full scale * Calibration is executed under the UVA light and compare with the standard UVA light meter. * Spec. tested under the environment RF Field Strength less than 3 V/M & frequency less than the 30 MHz only.
Sensor Structure	The exclusive UV photo sensor with the cosine correction filter.
Buttons. Switch	Power button, Zero button, Range switch
Sample Time	Approx. 1 sec.
Sensor Structure	Microprocessor circuit.
Over Range indication	Indication of " - - - - ".
Weight	251 g / 0.55 LB (including battery)
Operating Temperature	0 to 50 $^{\circ}\text{C}$.
Operating Humidity	Less than 85% R.H.
Power Supply	DC 9V battery, 006P, MN 1604 (PP3) or equivalent.
Power Consumption	Approx. DC 6 mA.
Size	Main instrument : 113 x 70 x 25 mm. Sensor probe head : 45 mm dia x 32 mm. Sensor probe handle : 125 x 24 mm dia.
Accessories Included	Instruction manual..... 1 PC. UV sensor probe..... 1 PC.
Optional Acc.	Soft carrying case, CA-52A, CA-03.

* Appearance and specifications listed in this brochure are subject to change without notice.

0808-UV340A

+982165565901

+982144584619

+989034119385

پتروفهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR