

PRODUCT INFORMATION

Penetrant Testing



MR® 85 Remover

پترو فرهان گستر جنوب



PRODUCT CHARACTERISTICS

- Pre-cleaner and penetrant remover
- Colourless
- Suitable for all metals and ceramics (suitability for plastics must be checked before use)
- Carrier medium Alcohol

APPROVALS / SPECIFICATION

- EN ISO 3452-2
- EN ISO 3452-6
- PMUC
- ASTM E165
- ASME Code V, Art. 6
- RCC-M
- TLV 9017 01:2011-01

SUGGESTED PRODUCTS

Approvals / Conformities acc. DIN EN ISO 3452-2:

Penetrant: For all penetrant typ I, II and III; not for System "HOT"
Developer: MR® 70, MR® 70 I (AMS), MR® 703 W (+5 °C)
Test block's: Reference-Testblock 1, Reference-Testblock 2 und ASTM Testblock

MINIMUM SHELF LIFE / TEMPERATURES

Aerosol/Bulk: 3 years at ambient storage temperature

Storage: +5 °C - +45 °C
Application: -10 °C - +50 °C

FGJ-NDT.IR
DIGINDT.IR

DELIVERY FORM



FURTHER INFORMATION

- Process description according to **EN ISO 3452-1** on request or on www.mr-chemie.de/en.
- For further information see Material Safety Data Sheet and certificate 3.1.
- For additional equipment please visit our Homepage or contact our sales team.

Tehran, Tehransar

+982165565901

+982144584619

+989034119385

18.11.2021

technical changes reserved!

1/1

MR CHEMIE
GmbH

MR Chemie GmbH
Nordstr. 61-63 · 59427 Unna
Tel. +49 (0)23 03 / 9 5151 - 0

www.mr-chemie.de