

UNI-T

UT15 SERIES Waterproof Type Voltage Testers UT15A ▪ UT15B ▪ UT15C



EN:61010-1
EN:61326-1
EN:61243-3



■ UT15A



■ UT15B



■ UT15C

SPECIFICATIONS

| Specifications | Range | Best Accuracy | | |
|----------------------------------|--|--|--|--|
| | | UT15A | UT15B | UT15C |
| Model | 12V 24V 50V | 0~12V 19V±2V 48V±6V | 0~12V 19V±2V 48V±6V | 0~12V 19V±2V 48V±6V |
| LED AC/DC Voltage Indication (V) | 120V 230V 400V 690V | 110V±20V 200V±20V 340V±30V 520V±30V | 110V±20V 200V±20V 340V±30V 520V±30V | 110V±20V 200V±20V 340V±30V 520V±30V |
| Phase Rotation Test | Operating Voltage: 0V~690V Frequency: 50Hz~60Hz | ✓ | ✓ | ✓ |
| Single Lead(L2)Voltage Detection | Operating Voltage: 0V~690V Frequency: 50Hz~400Hz | ✓ | ✓ | ✓ |
| Continuity Test | Resistance: 0~100KΩ Beeper and LED Light Indicator | | ✓ | ✓ |
| Polarity Detection | Positive & Negative | ✓ | ✓ | ✓ |
| Features | | | | |
| Water-Proof (IP65) | | ✓ | ✓ | ✓ |
| Auto Range | | ✓ | ✓ | ✓ |
| Work Light | | ✓ | ✓ | ✓ |
| Low Battery Indication | Short circuit two leads,LED and beeper off when the battery is low | ✓ | ✓ | ✓ |
| LCD AC/DC Voltage Display | 24V~690V | | | ±(3%+5) |

GENERAL CHARACTERISTICS

| | |
|------------------------------|---|
| Power | 1.5V Batteries (R03)×2 |
| LCD Size | UT15C-23mm × 12mm |
| Product Color | Red and Grey |
| Product Net Weight | 210g |
| Product Size | 275mm × 51mm × 30mm |
| Standard Accessories | Batteries |
| Standard Individual Packing | Blister, English Manual |
| Standard Quantity Per Carton | 30PCS |
| Standard Carton Measurement | 440mm × 295mm × 455mm (0.079 CBM Per Standard Carton) |
| Standard Carton Gross Weight | 17Kg |

DIGINDT.IR
FGJ-NDT.IR

+982165565901

+982144584619

+989034119385

Tehran, Tehransar