

UNI-T®



UT211B 60A Mini Clamp Meter



● UT211B



UT211B 60A mini clamp meter is a high precision tool designed with the resolution of 0.1mA. UT211B is perfect for anyone requiring high precision and accurate results when working with electronics, such as troubleshooting solar power systems current load, electrical cars, etc. It is ergonomically designed and also lightweight, making it a convenient tool for working in tight spaces.

SPECIFICATIONS

| | Range | UT211B |
|-------------------------|------------------------|------------|
| AC current (A) | 60A (0.1mA resolution) | ±(1.5%+10) |
| DC current (A) | 60A | ±(2%+3) |
| AC voltage (V) | 600V | ±(0.8%+3) |
| DC voltage (V) | 600V | ±(0.7%+3) |
| Resistance (Ω) | 60MΩ | ±(0.8%+2) |
| Capacitance (F) | 62mF | ±(4%+5) |
| Features | | |
| Display count | | 6000 |
| Auto range | | ✓ |
| True RMS | | ✓ |
| Diode test | Around 3.0V | ✓ |
| V.F.C. | | ✓ |
| NCV | | ✓ |
| Data hold | | ✓ |
| Zero mode | | ✓ |
| LCD backlight | | ✓ |
| Auto power off | Around 15 minutes | ✓ |
| Continuity buzzer | | ✓ |
| Low battery indication | ≤2.5V | ✓ |
| Input protection | | ✓ |
| Input impedance for DCV | ≥10MΩ | ✓ |

GENERAL CHARACTERISTICS

| | |
|------------------------------|--|
| Power | 1.5V battery (R03) x 2 |
| Display | 39.3mm x 26.5mm |
| Product color | Red and grey |
| Product net weight | 170g |
| Product size | 175mm x 60mm x 33.5mm |
| Standard accessories | Batteries, test leads |
| Standard individual packing | Gift box, carrying bag, English manual |
| Standard quantity per carton | 40pcs |
| Standard carton measurement | 385mm x 345mm x 305mm |
| Standard carton gross weight | 12.9kg |

DIGINDT.IR
FGJ-NDT.IR

+982165565901

+982144584619

+989034119385

Tehran, Tehransar