

New Product Gallery

UT302C



Enlarge

Download Manual



DIGINDT.IR
FGJ-NDT.IR

+982165565901

+982144584619

+989034119385

Tehran, Tehransar

Infrared Thermometers

SPECIFICATIONS

| Basic Functions | Range | Best Accuracy |
|----------------------------|--|---------------|
| Temperature Range | -32~650°C | |
| Display Accuracy | ± 1.8°C or ± 1.8% | |
| Repeatability | ± 0.5°C or 0.5% | |
| Display Resolution | 0.1 | |
| Distance to Spot Size | 20 : 1 | |
| Response Time | | |
| Spectral Response | | |
| Laser Power | wavelength 630-670 nm | |
| Display Hold | | |
| °C / °F Selection | ✓ | |
| Emissivity | | |
| Temperature Data Hold | ✓ | |
| Power | USB (Auto Double Display Backlight) or 9V Battery (6F22) | |
| Laser Switch | ✓ | |
| Search | ✓ | |
| Electricity Cut Off Memory | ✓ | |
| MAX, MIN temperatures | ✓ | |
| DIF, AVG temperatures | ✓ | |
| Double Display Backlight | EL | |
| Sleep Mode | ✓ | |
| Tripod mount | ✓ | |
| Low Battery Display | ✓ | |

GENERAL CHARACTERISTICS

| | |
|------------------------------|---|
| LCD Size | 32 x 29 mm |
| Product Color | Red and Grey |
| Product Net Weight | 270g |
| Product Size | 169 x 138 x 53 mm |
| Standard Accessories | Battery, English Manual, USB Cable |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 32 pcs |
| Standard Carton Measurement | 510 x 410 x 330 mm(0.069 CBM Per Standard Carton) |
| Standard Carton Gross Weight | 13kg |

*Available at Extra Cost
Specifications and other information are subject to change without further notice.

[Back to main menu](#)