

UNI-T®

UT320 SERIES
Contact Type Thermometers
 UT321 / UT322 / UT323 / UT325



CE EN 61326-1



■ UT321



■ UT322



■ UT323



■ UT325

SPECIFICATIONS

Specifications	Range	Best Accuracy				
		UT321	UT322	UT323	UT325	
Model		Single	Dual	Single	Dual	
Single or Dual Input						
Temperature	Type K	-200°C~1372°C (-328°F~2501°F)	±(0.5%+0.8)	±(0.5%+0.8)	±(0.2%+0.6)	±(0.2%+0.6)
	Type J	-210°C~1200°C (-346°F~2192°F)	±(0.5%+0.8)	±(0.5%+0.8)	±(0.2%+0.6)	±(0.2%+0.6)
	Type T	-250°C~400°C (-418°F~752°F)	±(0.5%+0.8)	±(0.5%+0.8)	±(0.2%+0.6)	±(0.2%+0.6)
	Type E	-150°C~1000°C (-238°F~1832°F)	±(0.5%+0.8)	±(0.5%+0.8)	±(0.2%+0.6)	±(0.2%+0.6)
	Type R	0.0°C~1767°C (+32°F~3212°F)			±(0.2%+2)	±(0.2%+2)
	Type S	0.0°C~1767°C (+32°F~3212°F)			±(0.2%+2)	±(0.2%+2)
	Type N	-200°C~1300°C (-328°F~2372°F)			±(0.2%+1.5)	±(0.2%+1.5)
Resolution	0.1°C(When Value >999.9°C:1°C)	✓	✓	✓	✓	
Features						
°C/°F/K Selection		✓	✓	✓	✓	
Data Hold		✓	✓	✓	✓	
Auto Power Off		✓	✓	✓	✓	
Low Battery Indication		✓	✓	✓	✓	
MAX Mode		✓	✓	✓	✓	
MIN Mode		✓	✓	✓	✓	
AVG Mode		✓	✓	✓	✓	
Data Storage		100	100	100	100	
USB Interface		✓	✓	✓	✓	
High Alarm				✓	✓	
Lower Alarm				✓	✓	
High/Lower Signal Output				✓	✓	
LCD Backlight		✓	✓	✓	✓	
Auto Calibration		✓	✓	✓	✓	
Electricity Cut-off Memory		✓	✓	✓	✓	

GENERAL CHARACTERISTICS

Power	USB or 9V Battery(6F22)
LCD Size	30mm x 32mm
Product Color	Red and Grey
Product Net Weight	270 g
Product Size	175mm x 85mm x 30mm
Standard Accessories	Battery,USB Interface Cable,PC Software CD,Type K Temperature Probe
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	565mm x 405mm x 302mm (0.069 CBM Per Standard Carton)
Standard Carton Gross Weight	19.5 Kg

DIGINDT.IR
 FGJ-NDT.IR

+982165565901

+982144584619

+989034119385

Tehran, Tehransar