


UNI-T®

UT681 Series Cable Testers



● UT681L

● UT681C

● UT681HDMI

SPECIFICATIONS

| | Range | UT681L | UT681C | UT681HDMI | Description |
|--------------------------|--|--------|--------|----------------|---|
| Test function | To test for: RJ45/RJ11 | √ | | | |
| | To test for: RJ45/RJ11/BNC | | √ | | Need to use RJ45 to BNC adaptor |
| | To test for: HDMI/Mini-HDMI | | | √ | |
| | Fast test mode | √ | √ | | LED1~LED8, LED_G |
| | Slow test mode | √ | √ | | LED1~LED8, LED_G |
| | Scan test mode | | | √ | LED1~LED19, LED_S |
| | Full display test mode | | | √ | LED1~LED19, LED_S |
| | To test for the case of short circuit, crossover, open circuit, etc. | √ | √ | √ | |
| | Ethernet cable: shielded/ unshielded test | √ | √ | √ | |
| | Manual shutdown function | √ | √ | √ | |
| | Auto shutdown function | √ | √ | √ | No operation within 10 minutes, the device will shut down automatically |
| | Single key operation | √ | √ | √ | |
| Power supply: 9V battery | √ | √ | √ | | |
| Low battery detection | √ | √ | √ | Less than 7.2V | |
| Application environment | Working temperature: 0~40°C | √ | √ | √ | |
| | Storage temperature: -10~50°C | √ | √ | √ | |
| | Working humidity: 20~80%RH | √ | √ | √ | |
| | Storage humidity: 10~90%RH | √ | √ | √ | |
| Safety standard | Altitude: ≤2000 meters | √ | √ | √ | |
| | CE EN61326-1: 2013; EN61326-2-2: 2013 | √ | √ | √ | |

GENERAL CHARACTERISTICS

| | |
|------------------------------|---|
| Product color | Red and grey |
| Product net weight | Transmitter: 87g; receiver: 51g |
| Product size | Transmitter: 102mm x 62mm x 28mm; receiver: 102mm x 37mm x 28mm |
| Standard accessories | 9V battery, BNC to RJ45 adaptor (UT681C) |
| Standard individual packing | Gift box, English manual |
| Standard quantity per carton | 40pcs |
| Standard carton measurement | 455mm x 410mm x 225mm |
| Standard carton gross weight | UT681L: 6.4kg; UT681C: 8.7kg; UT681HDMI: 9.5kg |

DIGINDT.IR
FGJ-NDT.IR

+982165565901

+982144584619

+989034119385

Tehran, Tehransar