

UT682 wire tracker consists of a transmitter and a receiver, it is able to track ethernet/telephone/power cables without opening their insulation. UT682 can troubleshoot ethernet cables and is a recommended tool for debugging communication cables and audio/video cables.



■ SPECIFICATIONS

Range		UT682	UT682D	
Wire tracking features	Wire types	LAN cable\telephone line\coaxial cable\electric wire	Telephone line\twisted-pair\electric wire	
	Indication light for signal strength	√		
	Live switchboard wire tracing	√		
	Switchboard wire tracing distance	≥100m		
	Telephone lines tracking distance	≥3000m	≥3000m	
	Unshielded cables tracking distance	≥320m		
	Shielded cables tracking distance	≥320m		
	Open and short circuit test	√		
	Polarity indication for telephone lines	DCV function, range: ±(5V-52V)	√	√
	Telephone lines and LAN cables distinction	Jacks distinction	√	
	Broken wire tracking	√		
	Transmitter output voltage	≥12V peak-peak	8V DC with a new battery	
	Transmitter low battery indication	6.6V±0.5V	7V±0.5V	
	Transmitter power supply	9V battery	√	
	Max transmitter working current	25mA		
Wire alignment	Headphone jack for receiver	√		
	Receiver power supply	9V battery	√	
	Max receiver standby current	~10mA	√	
	Max receiver operating current	<40mA (AC, RMS)	√	
Transmitter input voltage protection	Line sequence measurement	9 LEDs (LED1-LED8, LED_G)	√	
	Line sequence measuring speed	Fast and slow selectable	√	
	LAN cable: shielded/unshielded indication	√		
Operating environment	Operating temperature: 0~40°C; Storage temperature: -10~50°C Operating humidity: 20~75%RH; Storage humidity: 10~90%RH; Altitude: ≤2000m			

■ GENERAL CHARACTERISTICS

Product color	Red and grey
Product net weight	UT682: Transmitter-125g, receiver-153g; UT682D: Transmitter-150g, Receiver-130g
Product size	UT682: Transmitter-125mm x 48mm x 28mm, receiver-195mm x 48mm x 30mm UT682D: Transmitter-74mm x 68mm x 28mm, receiver-208mm x 47mm x 33mm
Standard accessories	9V battery x 2, RJ11 cable (UT682), RJ45 cable (UT682), RJ11 cable with alligator clips (UT682)
Standard individual packing	Blister (UT682), carrying bag (UT682), gift box (UT682D), English manual
Standard quantity per carton	UT682: 24pcs; UT682D: 20pcs
Standard carton measurement	UT682: 575mm x 310mm x 430mm; UT682D: 425mm x 265mm x 260mm
Standard carton gross weight	UT682: 12.3kg; UT682D: 7.5kg

Meraserw-5 s.c. 70-312 Szczecin ul. J.Bema 5, tel.(91)484-21-55, e-mail: handel@meraserw5.pl, sklep: www.meraserw5.pl, strona: www.meraserw.szczecin.pl

DIGINDT.IR
FGJ-NDT.IR

+982165565901

+982144584619

+989034119385

Tehran, Tehransar