



UNI-T

UT692/693 SERIES

OPTICAL POWER METERS/
OPTICAL MULTIMETER (POWER METER & VFL)



Applications:

- Cable construction and maintenance
- Optical fiber communication
- Evaluation of optical equipment
- Production, installation, operation and maintenance of fiber optic transmission systems
- Optical engineering, laboratory, production plant or facility maintenance



● UT692G

		Description	UT692D	UT692G	UT693D
Optical power meter	Wavelength range	800nm~1700nm			
	Calibrated wavelength	850nm, 980nm, 1300nm, 1310nm, 1490nm, 1550nm, 1625nm, 1650nm			
	Measurement range	UT692D/UT693D: -70~-10dBm, UT692G: -50~-26dBm			
	Uncertainty	±5%	√	√	√
	Display resolution	Linear: 0.1%, logarithmic: 0.01dBm			
	Connector	FC/SC/ST			
	Detector type	InGaAs			
Visual fault locator	Wavelength	650nm±10nm			
	Power	10mW (measurable optical fiber length: approximately 8~10km)			√
	Mode	Continuous/Pulse			
	Connector	FC/SC/ST			
Flashlight			√		
Features					
Low battery indication			√	√	√
Auto power off			√	√	√
IP rating			IP65	IP65	IP65
Drop test			2m	2m	2m
Power	1.5V battery (LR6) x 3				
Display	63mm x 40mm				
Product color	Red and grey				
Product net weight	300g				
Product size	189mm x 87mm x 45mm				
Standard accessories	Batteries, carrying bag				
Standard individual packing	Gift box, English manual				
Standard quantity per carton	10pcs				
Standard carton measurement	295mm x 250mm x 210mm				
Standard carton gross weight	5.66kg				

DIGINDT.IR
FGJ-NDT.IR

+982165565901

+982144584619

+989034119385

Tehran, Tehransar