

UT695D-10 OPTICAL MULTIMETER

UT695D-10 includes optical power meter, visual fault locator, flashlight, and remote cable tester. UT695D-10 is used for optical signal power measurement, optical fiber line loss test, optical device insertion loss test, optical fiber fault detection, optical fiber breakpoint location, end-to-end optical fiber identification and more. Designed with IP54 dust and water prevention function, UT695D-10 can be applied to optical cable construction and maintenance, optical fiber communication, optical fiber sensing, optical CATV and other fields.



		Description
Optical power meter	Wavelength range	800nm~1700nm
	Calibrated wavelength	850nm, 980nm, 1300nm, 1310nm, 1490nm, 1550nm, 1625nm, 1650nm
	Measurement range	-70~3dBm
	Uncertainty	±5%
	Display resolution	Linear: 0.1%, logarithmic: 0.01dBm
	Connector	FC/SC/ST
	Detector type	InGaAs
Visual fault locator	Wavelength	650nm±10nm
	Power	10mW (measurable optical fiber length: approximately 8~10km)
	Mode	Continuous/Pulse
	Connector	FC/SC/ST
Flashlight		√
LAN cable sequence test		Line sequence measurement (LED1~8, LED_G)
Features		
Low battery indication		√
Auto power off		√
IP rating		IP54
Drop test		2m
Power		1050mAh rechargeable battery
Display		42mm x 33mm
Product color		Red and grey
Product net weight		168g
Product size		132mm x 68mm x 31mm
Standard accessories		USB cable
Standard individual packing		Gift box, English manual
Standard quantity per carton		10pcs
Standard carton measurement		305mm x 270mm x 130mm
Standard carton gross weight		About 2.7kg

DIGINDT.IR
FGJ-NDT.IR

+982165565901

+982144584619

+989034119385

Tehran, Tehransar