

شرکت پترو فرهان گستر جنوب

Elcometer 101 Coating Thickness Gauge

The original non-destructive dry film thickness gauge, the Elcometer 101 was the world's first portable coating thickness gauge with the original being produced in 1947.

- Insensitive to hot and cold surfaces - ideal for hot sprayed metal coatings
- Incorporates reading hold feature
- Accuracy of $\pm 10\%$
- Ideal for hazardous areas



STANDARDS:

AS 2331.1.3, ASTM B 499, ASTM G 12, BS 5411-11, ISO 2178, JIS K 5600-1-7, SSPC PA2

Technical Specification

Part Number	Description	Scale Range	Certificate
A101A-01A	Elcometer 101 Mechanical Coating Thickness Gauge	0 - 600 μ m (0 - 25mils)	o
Operating Plane	90° to substrate		
Minimum Measurement Area	38 x 15mm (1.5 x 0.6")		
Minimum Measurement Diameter	25mm (1") (on bar material)		
Accuracy	$\pm 10\%$ of the reading or 2.5 μ m (0.1mil) whichever is the greater		
Packing List	Elcometer 101, calibration foils, carry case, wrist harness and operating instructions		

o Optional Calibration Certificate available.

+982165565901

+982144584619

+989034119385

Tehran, Tehransar