

Hand-held Conductivity · TDS · Salt · Temp Meter

Features

- Microprocessor based designed.
- Large displays reading and Temperature simultaneously.
- Splash proof housing and rubber protective holster.
- Automatic Temperature Compensation(ATC) or Manual Temperature Compensation(MTC)
- Simple to calibrate by one keyboard for 5 points standard solutions.
- Auto shut off after 10 minutes of non use.



CD-104

Specifications

CD-104				
	Cond.	TDS	Salt	Temp.
Range	0.0~ 199.9 μ S 200~ 1999 μ S 2.00~ 19.99 mS 20.0~ 100.0 mS@25 $^{\circ}$ C	0.0~131.9 ppm 132~1319 ppm 1.32~13.19 ppt 13.2~66.7 ppt	0.0~99.9 ppm 100~999 ppm 1.00~9.99 ppt 10.0~50.0 ppt	0~110 $^{\circ}$ C
Accuracy	\pm 2% FS			
Resolution	0.1/1 μ S/0.01/0.1 mS	0.1/1ppm/0.01/0.1 ppt	0.1/1ppm/0.01/0.1 ppt	0.1 $^{\circ}$ C
Compensation	ATC 0-50 $^{\circ}$ C			
Power	9V or AC adaptor			
Dimension	108 x 75 x 30 mm			
Weight	135 g (with battery)			

Standard Accessories

- Conductivity cell
- Temperature probe
- 1413uS solution x 50ml
- 12880 uS x 50ml
- 9V battery



www.gondo.com.tw



+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR