

4 ranges

Tehran, Tehransar



CONDUCTIVITY METER

Model : CD-4306

ISO-9001, CE, IEC1010

پترو فرهان گستر جنوب

FEATURES




Lutron

- * 4 rings conductivity probe, high performance, wide range, professional.
- * 4 ranges : 200 uS, 2 mS, 20 mS, 200 mS.
- * Separate electrode, easy operation.
- * The portable conductivity meter provides fast, accurate readings, with digital readability and the convenience of a remote probe separately.
- * All function keys are used the rubber button.
- * Data hold.
- * Used the durable, long-lasting components, including a strong, light weight ABS-plastic housing case.
- * Wide applications: water conditioning, aquariums, beverage, fish hatcheries, food processing, photography, laboratory, paper industry, plating industry, quality control, school & college.

LUTRON ELECTRONIC

The Art of Measurement



+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR

4 ranges

CONDUCTIVITY METER

Model : CD-4306

Tehran, Tehransar

پتروفرهان گستر جنوب



FEATURES

- * 4 rings conductivity probe, high performance, wide range, professional.
- * 4 ranges : 200 uS, 2 mS, 20 mS, 200 mS.
- * Separate electrode, easy operation.
- * The portable conductivity meter provides fast, accurate readings, with digital readability and the convenience of a remote probe separately.
- * LCD display for low power consumption & clear read-out even in bright ambient light condition.
- * Water resistance on the front panel.
- * All function keys are used the rubber button.
- * Data hold.
- * Used the durable, long-lasting components, including a strong, light weight ABS-plastic housing case.
- * Built-in Low battery indicator.
- * Wide applications: water conditioning, aquariums, beverage, fish hatcheries, food processing, photography, laboratory, paper industry, plating industry, quality control, school & college.

SPECIFICATIONS

Display	Large LCD display, 21.5 mm digit height.
Measurement & Range	4 ranges : 200 uS, 2 mS, 20 mS, 200 mS.
Resolution	0.1 uS for 200 uS range. 0.001 mS for 2 mS range. 0.01 mS for 20 mS range. 0.1 mS for 200 mS range. * uS - micro Simens * mS - milli Simens
Accuracy (23 ± 5 °C)	± (1% F.S. + 1 d) * F.S. - Full scale
Sampling Time	Approx. 0.4 second.
Over Range Indicator	Display shows " 1 ".
Data Hold	To freeze the measured pH value on the display.
Temperature Compensation	Automatic, 0 to 50 °C (32 to 122 °F). Temperature compensation factor fix on fix on 2% per °C.
Calibration VR	Build in external calibration VR.
Operating Temperature	0 to 50 °C (32 to 122 °F).
Operating Humidity	Max. 80% RH.
Power Supply	DC 9V battery (heavy duty type). 006P, MN1604(PP3) or equivalent.
Power Current	Approx. DC 5 mA.
Weight	270 g/0.60 LB (w/battery & electrode).
Dimension	<i>Meter :</i> 200 x 68 x 30 mm (7.9 x 2.7 x 1.2 inch). <i>Electrode :</i> Round, 20 mm Dia. x 124 mm length.
Accessories Included	Instruction Manual..... 1 PC. Conductivity electrode..... 1 PC. Hard Carrying Case.....CA-06
Optional Accessory	1.413 mS calibration solution..... CD-14

* Appearance and specifications listed in this brochure are subject to change without notice.

0403-CD4306

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR