

# UNI-T®

## UT380 Series Light Meters



UT380 series light meters measure light intensity and display results in Lux or Fc. It has a high sampling rate of 100/s.

UT380 series' low power consumption allows up to 200 hours of continuous operation. Results can be stored within the device and transferred to PC for further analysis, printing and storage.

### SPECIFICATIONS

	Range	UT381	UT382
Illuminance measurement (Lux)	20 Lux	±(3%+20)	±(3%+20)
	200 Lux	±(3%+8)	±(3%+8)
	2000 Lux	±(3%+8)	±(3%+8)
	20000 Lux	±(3%+8)	±(3%+8)
Illuminance measurement (Fc)	2 Fc	√	√
	20 Fc	√	√
	200 Fc	√	√
	2000 Fc	√	√
<b>Features</b>			
Display count		2000	2000
Auto range		√	√
Data hold		√	√
Auto power off	Around 10 minutes	√	√
Low battery indication	Around ≤7.1V	√	√
MAX/MIN mode		√	√
Data storage		2044	2044
USB interface			√
Auto record time setup		√	√
Real-time clock		√	√



DIGINDT.IR  
FGJ-NDT.IR

● UT382

### GENERAL CHARACTERISTICS

Power	9V battery (6LF22)
Display	22.5mm x 32.5mm
Product color	Red and grey
Product net weight	185g
Product size	195mm x 45mm x 26mm
Standard accessories	Carrying bag, USB interface cable (UT382), PC software CD (UT382)
Standard individual packing	Blister, gift box, English manual
Standard quantity per carton	20pcs
Standard carton measurement	447mm x 300mm x 335mm
Standard carton gross weight	7kg

+982165565901

+982144584619

+989034119385

Tehran, Tehransar