

UNI-T®

UT383/UT383 BT Series Mini Light Meters



UT383/UT383BT can effectively measure light intensity and display results in units of Lux or FC on screen. UT383BT can transfer measurement data through bluetooth to UNI-T's custom mobile APP (iENV) for further analysis, storage, and export. iENV can be downloaded from Google Play, Apple Store, or UNI-T's website by searching 'iENV'.

SPECIFICATIONS

	UT383	UT383BT
Illuminance measurement (LUX)	0-199,900Lux	0-199,900Lux
Illuminance measurement (FC)	0-18,500Fc	0-18,500Fc
Accuracy	0-9999Lux/0-999Fc: ±(4%+8)	
	≥10000Lux/≥1000Fc: ±(5%+10)	
	≥100000Lux/≥9999Fc: ±(5%+10)	
Resolution	1Lux (0-9999Lux)	
	10Lux (≥10,000Lux)	
	100Lux (≥100,000Lux)	
	1Fc (0-9999Fc); FC=Lux/10.76 10Fc (≥10,000Fc); FC=Lux/10.76	
Sampling time	0.5s	
Features		
APP		✓
Bluetooth®		✓
Overload indication	OL	OL
MAX/MIN	✓	✓
Data hold	✓	✓
LCD backlight	✓	✓
Auto power off	✓	✓
Low battery indication	✓	✓
Tripod mounting hole		✓



● UT383 BT

GENERAL CHARACTERISTICS

Power	1.5V battery (R03) x 3
Display	32mm x 26mm
Product color	Red and grey
Product net weight	118g
Product size	160mm x 50mm x 28mm
Standard accessories	Batteries
Standard individual packing	Blister, English manual
Standard quantity per carton	UT383: 40pcs; UT383 BT: 20pcs
Standard carton measurement	UT383: 505mm x 330mm x 280mm UT383 BT: 332mm x 262mm x 290mm
Standard carton gross weight	UT383: 8.42kg; UT363 BT: 4.2kg

+982165565901

+982144584619

+989034119385

Tehran, Tehransar