



[Download Manual](#)

[Download Software](#)

SPECIFICATIONS

| Basic Functions | Range | Best Accuracy |
|--|--|---------------|
| DC Voltage | 400mV/4V/40V/400V/1000V | ± (0.025%+5) |
| AC Voltage | 4V/40V/400V/1000V | ± (0.4%+30) |
| DC Current | 400µA/4000µA/40A/400mA/10A | ± (0.08%+8) |
| AC Current | 400µA/4000µA/40A/400mA/10A | ± (0.5%+15) |
| Resistance | 400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ | ± (0.3%+8) |
| Capacitance | 40nF/400nF/4µF/40µF/400µF/4mF/40mF | ± (1%+20) |
| Temperature (°C) | -40°C ~ 1000°C | ± (1%+30) |
| Temperature (°F) | -40°F ~ 1832°F | ± (1.5%+50) |
| Frequency | 40Hz/400Hz/4kHz/40kHz/400kHz/4MHz/40MHz/400MHz | ± (0.01%+8) |
| Duty Cycle | 10%~90% | ± (1%+30) |
| 4~20mA Loop | 0~100% | ± (1%+50) |
| Power Measurement | | ± (2%+5) |
| Special Functions | | |
| Fused 10A Range | | ✓ |
| Auto Ranging | | ✓ |
| Current Measurement Alarm | | ✓ |
| Function Set Up | | ✓ |
| Voltage & Current : AC + DC Measurement | | ✓ |
| Data Logging | | 100 |
| Data Recall | | ✓ |
| Diode | | ✓ |
| Continuity Buzzer | | ✓ |
| True RMS | | ✓ |
| Peak Hold | | ✓ |
| Max/Min Mode | | ✓ |
| Relative Mode | | ✓ |
| Data Hold | | ✓ |
| USB | | ✓ |
| Double Display Backlight | | ✓ |
| Full Icon Display | | ✓ |
| Sleep Mode | | ✓ |
| Low Battery Display | | ✓ |
| Input Impedance for DC Voltage Measurement | DC 200mV : Around 2.5GΩ All Other Ranges : 10MΩ | ✓ |
| Max. Display | 40000 | ✓ |
| Analogue Bar Graph | | ✓ |

GENERAL CHARACTERISTICS

| | |
|------------------------------|---|
| Power | 9V Battery (6F22) |
| LCD Size | 73 x 50 mm |
| Product Colour | Red and Grey |
| Product Net Weight | 384g |
| Product Size | 200 x 93 x 40mm |
| Standard Accessories | Test Lead, English Manual, Battery, Alligator Clip, USB Interface Cable, Software, Point Contact Temperature, Probe, Carrying Bag, Test Clip, Power Adaptor |
| Optional Accessories* | Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2) |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 20 pcs |
| Standard Carton Measurement | 542 x 376 x 388mm (0.079 CBM Per Standard Carton) |
| Standard Carton Gross Weight | 18kg |

+982165565901

+982144584619

+989034119385

Tehran, Tehransar