

## Ultrasonic Thickness Gauge WT100A

### Specification:

Measuring range	1.00 to 225.0mm (0.039 to 8.85 inches)
Data storage	500 Data
Transducer (Probe) Type	5MHz, 10 mm
Measurement error	$\pm(0.5\%H + 0.05)$ mm
Resolution	0.01 mm
Lower limit of pipe measurement	$\Phi$ 20x3mm (steel)
Adjustable range of velocity	1 000~9999m/s
Operation environment	Temperature:0~40°C(32~104°F) Humidity:20%~90%RH
Power	3* 1.2V NiMH Rechargeable Batteries
Dimensions	146 x 65 x 30 mm 5.75 x 2.56 x 1.18 inches
Weight	130 gram with batteries



### Features:

- ✓ Measuring the thickness and the sound speed of various materials.
- ✓ High contrast 2.4" color-screen HD display with backlit & 5 selectable color display
- ✓ Auto calibration
- ✓ Units: mm/inch
- ✓ Storage data (up to 500 data) and recall function
- ✓ Statistic view (Min/Max/Avg/High/Low)
- ✓ Automatic shutdown
- ✓ Built in metal calibration block

### Package List:

- 1 x Main device
- 1 x Transducer (probe)
- 3 x Rechargeable batteries (1.2V per)
- 1 x USB cable
- 1 x Charger (5V, 1A)
- 1 x Hard Carrying case
- 1 x English User Manual

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR