

**wintact®**

MODEL: WT8806

## Carbon Monoxide Monitor Instruction Manual



Version: WT8806-EN-01

+982165565901

پتروفرهان گستر جنوب

+982144584619

FGJ-NDT.IR

+989034119385

DIGINDT.IR

Gas detection	CO
Measuring range	0~1000 $\mu$ mol/mol
Resolution	1
Accuracy	When the measuring range is (0 ~ 50) $\mu$ mol/mol, maximum allowable error is: 5 $\mu$ mol/mol
	When the measurement range is (50 ~ 1000) $\mu$ mol/mol, maximum allowable error is: 10%
Response time (90%)	Less than 30 seconds
Indication mode	LCD displays real-time data and system state, LED, sound, vibration indication alarm
Storage Conditions	Temperature: -10~55°C; Humidity: < 85%RH
Operation Conditions	Temperature: - 20~50°C; Humidity: <95%RH non-condensing
Working voltage	DC 3.7V (Lithium battery capacity 1800mAh)
Battery Model	LP103450-1800mAh
Charging time	6~8h
Standby time	More than 8h on end (slightly change with working state)
Dimensions	71*153*49mm
Weight	215.4g(with battery and back button)

Accessory name	Quantity
Carbon Monoxide Monitor (Contain Alligator clips)	1PCS
Cover	1PCS
With screws	1PCS
Transparent trachea	1PCS
Charger	1PCS
Data line	1PCS
Manual	1PCS
Packing box	1PCS