



پتروفرهان گستر جنوب

Tehran, Tehransar

wintact®

MODEL: WT8811

Compound Gas Monitor Instruction Manual



Standard:Q/HTY 010-2018 Q/HTY 011-2018
Q/HTY 012-2018 Q/HTY 007-2018

پتروفرهان گستر جنوب

Specifications

Compound Gas Monitor range			
Measuring item	Unit	Range	Resolution
Combustible gas LEL	%LEL	0~100	0.1
Oxygen O ₂	%VOL	0~30	0.1
Hydrogen sulfide H ₂ S	μmol/mol	0~100	0.1
Carbon monoxide CO	μmol/mol	0~1000	1

Accuracy	≤ ±5%FS
Response time (90%)	Less than 30 seconds
Indication mode	LCD displays real-time data and system state, LED, sound, vibration indication alarm
Storage Conditions	Temperature:-10~55°C; Humidity:<85%RH
Operation Conditions	Temperature:- 20~50°C; Humidity:< 95%RH non-condensing
Working voltage	DC 3.7V (Lithium battery capacity 1800mAh)
Charging time	6~8h
Standby time	More than 8h on end (slightly change with working state)
Dimensions	71*153*49mm
Weight	218.7g With battery

☎ +982165565901

☎ +982144584619

☎ +989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR