


1. Instruction to structure

پترو فرهان گستر جنوب

Tehran, Tehransar

Thermal Imaging Camera



- 160x120     220x160     320x240

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR

File format	JPG
USB	Micro USB 2.0
Power supply	Built-in chargeable 18650 battery
Working time	2-3 hours
Automatic power-off time	Selectable: 5 minutes/20 minutes/ not power off automatically
Setting command	Unit, language, date, time, information
Language	English, Chinese, Italian, German
Product size	225mm×69.3mm×93.7mm
Product weight	323g
Work temperature	0°C to 45°C
Storage temperature	-20°C to 60°C
Relative humidity	< 85%RH

Display screen	2.8 " full angle TFT display creen		
Infrared image resolution	160×120	220×160	320×240
Field angle	35°×26°	35°×26°	56°×42°
Temperature measurement range	-20°C to 450°C (-4°F to 842°F)		-20°C to 300°C (-4°F to 572°F)
Measurement accuracy	±2°C/±2% (Greater than 300 °C accuracy is ± 5%)		±2°C/±2%
Visible image resolution	300,000 pixel		
LCD resolution	320×240		
Shortest focusing distance	0.5M		
Shortest focusing distance	70mK		
Emissivity	Adjustable from 0.01 to 1.00		
Frame rate of thermal images	9Hz		
Wavelength coverage	8-14um		
Focus mode	Fixed		
Color palette	Rainbow, iron oxide red, cold color, black & white, white & black		
Storage capacity	Built-in 3G (above 20 thousand image stored)		

 **+982165565901**

 **+982144584619**

 **+989034119385**

پتروفرهان گستر جنوب

**FGJ-NDT.IR**

**DIGINDT.IR**