

DIGITAL CLAMP METERS AC



KEW 2200/2200R



- Ultra Slim and lightweight Handy design
- $\phi 33\text{mm}$ Tear Drop Jaw easy to use in tight places.
- 1000A AC Clamp Meter
- DMM function ACV, DCV, Ω , Continuity Buzzer.
- Fuseless electronic protection on Ω up to 600V
- DMM function ACV, DCV, Ω , Continuity Buzzer.
- Safety Standard IEC 61010-1, 61010-2-032 CAT IV 300V* / CAT III 600V *2200R only
- Minimum resolution 0.01A

photo : 2200R

	2200	2200R
Detection method	Averaging value	True RMS value
AC A	40.00/400.0/1000A (Auto-ranging) $\pm 1.4\% \text{rdg} \pm 6 \text{dgt}$ (50/60Hz) $\pm 1.6\% \text{rdg} \pm 6 \text{dgt}$ (45 - 65Hz)	40.00/400.0/1000A (Auto-ranging) $\pm 1.5\% \text{rdg} \pm 5 \text{dgt}$ (45 - 65Hz) $\pm 2.0\% \text{rdg} \pm 5 \text{dgt}$ (40Hz - 1kHz)
AC V	4.000/40.00/400.0/600V (Auto-ranging) $\pm 1.8\% \text{rdg} \pm 7 \text{dgt}$ (45 - 65Hz) $\pm 2.3\% \text{rdg} \pm 8 \text{dgt}$ (65 - 500Hz)	
DC V	400.0mV/4.000/40.00/400.0/600V (Auto-ranging) $\pm 1.0\% \text{rdg} \pm 3 \text{dgt}$ * *400mV range is excluded	
Ω	400.0 Ω /4.000/40.00/400.0k Ω /4.000/40.00M Ω (Auto-ranging) $\pm 2.0\% \text{rdg} \pm 4 \text{dgt}$ (0 - 400k Ω) $\pm 4.0\% \text{rdg} \pm 4 \text{dgt}$ (4M Ω) $\pm 8.0\% \text{rdg} \pm 4 \text{dgt}$ (40M Ω)	
Continuity buzzer	buzzer sounds below 50 $\pm 30\Omega$	
Conductor size	$\phi 33\text{mm}$ max.	
Applicable Standards	IEC 61010-1 CAT IV 300V*, CAT III 600V Pollution degree2(AC A) *2200R only CAT III 300V, CAT II 600V Pollution degree2(AC/DC V) IEC 61010-031, IEC 61010-2-032, IEC 61326(EMC)	
Power source	R03/LR03(AAA)(1.5V) $\times 2$	
Continuous measuring time	Approx.350 hours	Approx.120 hours
Dimensions	190(L) \times 68(W) \times 20(D)mm	
Weight	Approx.120g(including batteries)	
Accessories	7107A (Test leads), 9160 (Carrying case), R03(AAA) $\times 2$, Instruction manual	

DIGITAL CLAMP METERS AC

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR