

KEW **5204** **NEW** / **5204BT** **NEW**

DIGITAL LIGHT METER



DATA HOLD MAX/MIN Bluetooth

photo : 5204BT

	5204/5204BT
Measuring Range	0.0 - 199900 lx
Ranges	199.9/1999/19990/199900 lx
Accuracy	$\pm 4\% \text{rdg} \pm 5 \text{dgt}$ (23°C $\pm$ 2°C)
Angle deviation from cosine characteristics	10° $\pm$ 1.5% 30° $\pm$ 3% 60° $\pm$ 10% 80° $\pm$ 30%
Relative spectral sensitivity characteristics	Deviation from spectral luminous efficiency: 9% or less
Response time	Auto range: 5s or less Manual range: 2s or less
Operation Temperature/Humidity	0°C - 40°C, 80%RH or less (without condensation)
Storage Temperature/Humidity	-10°C - 60°C, 70%RH or less (without condensation)
Communication Interface	Bluetooth® 5.0*, Android™ 5.0 or later, iOS 10.0 or later
Applicable Standards	IEC 61326 , JIS C 1609-1:2006
Power source	LR/R6(AA)(1.5V) $\times$ 2
Dimensions	169(L) $\times$ 63(W) $\times$ 37(D)mm
Weight	210g approx.
Accessories	9195(Carrying case) LR6(AA) $\times$ 2 Instruction Manual

\*5204BT only.

Some countries regulate the compliance with their Radio Law of the products equipped with Bluetooth®. Please confirm it with your distributor before purchasing our products equipped with Bluetooth®.



- Detachable & Rotatable Light Sensor
- Data Hold Function
- MAX/MIN Function
- Large LCD with BackLight

KEW CONNECT

Wireless communication with smartphone or tablet (Only 5204BT)

Use the application KEW Smart\* to improve work efficiency.

Download and install our special application "KEW Smart\*" in your smartphone or tablet device for logging the measured values. Measured values can be saved in your smartphone or tablet device in csv format: the data is editable in excel format.



+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR