



# 1333/1333R SOLAR POWER METER

## FEATURE:

- Wide spectral range.
- Excellent long term stability.
- Cosine corrected.
- Automatic transmission measurements.
- Select either power or transmission.
- Solar energy measurement.
- Current time setting function.
- User calibration factor setting function.
- End-mount light sensor.
- Select either  $W/m^2$  or  $Btu / (ft^2 \times h)$  units.
- Data Hold/MAX/MIN/AVG modes.
- Data Memory and Read function. (99 sets)
- Auto Data Memory and RS232 interface to PC. (TES-1333R)

## APPLICATIONS

- Meteorology.
- Agriculture.
- Solar radiation measurement.
- Solar power research.
- Physics and optical laboratories.
- Solar transmission measurement.
- Identify high performance windows.

## SPECIFICATIONS

Display	3-1/2 digits. Max. indication 1999
Range	2000 $W/m^2$ 634 $Btu / (ft^2 \times h)$
Resolution	1 $W/m^2$ 1 $Btu / (ft^2 \times h)$
Spectral response	400-1100nm
Accuracy	Typically within $\pm 10 W/m^2$ [ $\pm 3 Btu / (ft^2 \times h)$ ] or $\pm 5\%$ , whichever is greater in sunlight; Additional temperature induced error $\pm 0.38 W/m^2/^\circ C$ [ $\pm 0.12 Btu / (ft^2 \times h)/^\circ C$ ] from $25^\circ C$
Angular accuracy	Cosine corrected $< 5\%$ for angles $< 60^\circ$
Drift	$< \pm 2\%$ per year
Calibration	User recalibration available
Over-Input	Display shows "OL"
Sampling Time	Approx. 0.4 second
Manu Data Memory and Read	99 sets
Auto Data Memory	32000 sets (TES-1333R)
Battery	4 pcs size AAA
Battery Life	Approx. 100 hours
Operating Temp and Humidity	$0^\circ C$ to $50^\circ C$ ( $32^\circ F$ to $122^\circ F$ ) below 80%RH
Storage Temp and Humidity	$-10^\circ C$ to $60^\circ C$ below 70%RH
Weight	Approx. 165g
Dimension	111(L) x 64 (W) x 34(H) mm
Accessories	Carrying Case, Operation Manual, 4 pcs size AAA, RS232 cable (for TES-1333R), CD software (for TES-1333R)



## TES ELECTRICAL ELECTRONIC CORP.

7F, No.31 Lane 513, Rui Guang Rd., Neihu Dist, Taipei, Taiwan

Tel : (02) 2799-3660 Fax : 886-2-2799-5099

E-mail : tes@ms9.hinet.net <http://www.tes.com.tw>

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR