

# TES 1336A Datalogging Light Meter (USB)



## FEATURES

- Spectrum of photo sensor meets C.I.E. photopic curve V(λ)
- 16000 Records Data logging capacity
- USB interface (software included)
- Measurement of luminous intensity (PC Software)



## SPECIFICATION

<b>Measuring range</b>	20/200/2000/20000 Lux, 20/200/2000/20000 Fc
<b>Luminous intensity (cd)</b>	Intensity = illuminance x (length) <sup>2</sup>
<b>Length</b>	feet (Fc) meter (Lux)
<b>Resolution</b>	0.01 Lux
<b>Accuracy</b>	±( 3% rdg + 5dgts ) (calibrated to standard incandescent lamp, 2856 K)
<b>Overrange display</b>	OL
<b>Record (Data logging)</b>	16000 Point Data logger
<b>Sensor</b>	Silicon photo diode
<b>Sensor lead length</b>	150cm (approx)
<b>Sensor probe</b>	100(L) x 60(W) x 27(H) mm
<b>Power source</b>	One 9V battery
<b>Battery life</b>	50hrs (approx)
<b>Operating Storage Condition</b>	0 o C ~ 40 o C ( 32 o F~104 o F ) below 80% RH -10 o C ~ 60 o C ( 14 o F~140 o F ) below 70% RH
<b>Dimensions</b>	146(L) x 70(W) x 39(H) mm
<b>Weight</b>	300g (approx)
<b>Accessories</b>	Carrying case ∙ 9V battery ∙ instruction manual ∙ Software ∙ USB cable ∙ changer screwdriver.

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR