

Humidity Temperature Meter/Barometric pressure

Tehran, Tehransar



TES-1362

Printing Humidity Temperature Meter

Product Features

- Triple LCD Display for RH% Humidity, T1 for Air Temperature and T2 Type K Thermometer (-200°C ~ 1333°C)
- Dew Point Reading
- Max / Min / Data Hold
- Real Time Stamp
- Periodically Print out from Pre-Set time Interval

SPECIFICATIONS:

Measuring Range	Humidity : 10%RH ~ 95%RH T1 Temperature : -20°C ~ 60°C (- 4°F ~ 140°F) T2 (Type K) : -200°C ~ 1333°C (-328°F ~ 2431°F) Dew Point : -44°C ~ 58.5°C (-47.2°F ~ 137.3°F)
Resolution	-200°C ~ 999°C : 0.1°C -328°F ~ 999°F : 0.1°F other is 1°C/1°F
Accuracy	Humidity: ±3%RH (25°C, 20 ~ 80%RH) ±4%RH (25°C, 10 ~ 20%RH及80 ~ 90%RH) ±5%RH (25°C, 0 ~ 10% RH及90 ~ 100%RH) T1 Temperature: ±0.4°C (at +5°C to +60°C) ±0.8°C (at -20°C to 5°C and +60°C to +80°C) ±0.8°F (at +41°F to +140°F) ±1.6°F (at -4°F to 41°F and +140°F to +176°F) T2 Temperature: -50°C ~ -200°C : ±(0.2%rdg + 1.8°C) -50°C ~ 500°C : ±(0.1%rdg + 0.8°C) 500°C ~ 1333°C : ±(0.2%rdg + 1.8°C) -58°F ~ -328°F : ±(0.2%rdg + 3°F) -58°F ~ 1000°F : ±(0.1%rdg + 1.6°F) 1000°F ~ 2431°F : ±(0.2%rdg + 3°F) Dew Point: 1.0°C / 1.8°F
Sampling Rate	1 time/sec
Operating Conditions	0°C to 50°C (32°F to 122°F) below 95% RH
Power Source	6 pcs size AAA Alkaline Battery or 9V DC adaptor/500mA minimum.
Battery Life	Approx. 90 hours. (interval printing = 60 minute, not including beeper). 100 hours (except printing & beeper).
Size	193(L) ×74(W) ×37(H)mm
Weight	Approx. 430g with batteries & thermo-paper
Accessories	Carrying case, Instruction manual, Battery, type K probe (TP-K01), Two rolls thermo-paper.

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR