



TES-1380K PH / ORP / Temperature Meter

Product Features

- 0.001 pH resolution.
- Auto / Manual pH & Temperature Calibration.
- Auto / Manual Temperature Compensation.
- Auto-recognition of buffer solutions.
- A for one time test and continuous test.
- Display pH or mV with temperature Simultaneously.
- Fast & Easy pH measurement.
- Dual way RS-232 interface with software.
- Single recording: 99 records.
- Continuous recording: Have 99 sets of records, MAX. 3000 points.
- Indication of pH Electrode status.

Display	4 1/2 digital LCD display
Measurement Range	pH - 0 ~ 14 pH mV - 0 ~ 2000mV Temp - 0 °C ~ 100 °C (32 °F ~ 200 °F)
Resolution	pH - 0.001 pH mV - 0.1 mV Temp - 0.1 °C (0.1 °F)
Accuracy	pH - ±0.01 pH mV - ± (0.05% + 1d) Temp - ± 0.5 °C (0.9 °F)
Calibration date	Record the last data of adjustment
Data output	RS232 PC serial interface (Dual-way)
Operating / Storage Temp & Humidity	0°C to 50°C < 80%RH / -10°C to 60°C < 70% RH
Power Supply & Battery Life	"AA"-1.5V x 6 [Approx. 120 hours]
Dimensions & Weight	187(L)×73(W)×53(H)mm & 320g (7.58oz)
Memory recall	Single recording : 99 records. Continuous recording : Have 99 sets of records, MAX. 3000 points.
Applications	Stains, Lotion, Chemical, Brew, Bacteriology, Filthy water, Pulp, Pharmacy, Ferment, Electroplate, Drink, Aquaculture etc.
Accessories	Carrying case, Instruction manual, Software, Batteries, RS-232 Cable.
Optional Accessories	BS4 - pH4 buffer solution BS7 - pH7 buffer solution PH-200 - pH electrode PT-100 - Temperature probe

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR