

# TES-1601 Auto Ranging Insulation Tester



## FEATURES

- 4000M  $\Omega$  /1000V, 4000M  $\Omega$  /500V, 4000M  $\Omega$  /250V
- Power lock for 3 minutes  
(Auto power off)
- Auto-Zero adjustment
- Data-Hold-Function



## SPECIFICATION

### AC Voltage

Range	600V
Resolution	0.1V
Accuracy	1.5% rdg + 3 dgts
Input Impedance	4.5M $\Omega$
Overload Protection	750Vrms

### OHMS & Continuity Beeper

Range	40 $\Omega$
Resolution	0.1 $\Omega$
Accuracy	1% rdg + 5 dgts
Max open circuit voltage	12.8V
Overload protection	220Vrms

### MEG OHMS

Range	4000M $\Omega$ /250V, 4000M $\Omega$ /500V, 4000M $\Omega$ /1000V
Resolution	1K $\Omega$
Accuracy	3% rdg + 3 dgts
Terminal Voltage	250V ~ 1000V $\pm$ 2% ~ -0%
Output short circuit current	0.4mA/0.9mA/1.7mA max
Operating/Storage Condition	0 $^{\circ}$ C to 40 $^{\circ}$ C < 80% R.H. -10 $^{\circ}$ C to 60 $^{\circ}$ C < 70% R. H.

### General Specification

Power Source	8pcs "AA" 1.5V batteries
Sampling Rate	2.5 times/sec, Auto-Zero adjustment
Size	190mm(L)x140mm(W)x77mm(H)
Weight	900g
Accessories	Carrying Case, Test Lead, Battery & Instruction Manual

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR