



PROVA 135 LoopThermo®

4-20mA Loop Calibrator + Thermometer

CE

Features:

1. **Source 4~20mA, 0~24mA** with 1 μ A resolution (1K Ω load, 24V loop supply), basic accuracy 0.025%.
2. **Source 0~24.000V** with 1mV resolution.
3. **Source frequency 1~20000Hz** square wave with programmable duty cycle (1~99%).
4. **Auto step and auto ramp** for sourcing mA, V.
5. Easy fixed 25% up and down, or programmable percentage (1~99%) increase and decrease (mA, V).
6. **Measure DC mA** with loop power (24V output).
7. **Measure DC V**.
8. **Measure Temperature** ($^{\circ}$ C, $^{\circ}$ F) of 11 types of thermocouples (K, J, E, T, R, S, N, L, U, B and C).
9. Calibrator grade precision temperature measurement with 0.1 $^{\circ}$ C & 0.1 $^{\circ}$ F resolution.
10. Detection of thermocouples disconnection.
11. Source and Measure at the same time.
12. Warning for overload, output open (mA) or short (V).
13. Short circuit protection for output.
14. Battery power indication (%) when turn on the calibrator.

Applications:

1. **Calibration of 4~20mA** panel meters.
2. **LED brightness testing (0~24mA)**.
3. **Temperature calibration** of panel meters or instruments for 11 types of thermocouples.

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR



Electrical Specifications:

(23+/- 5°C, 10 minutes after turning on the power)

DC mA SOURCE (Max. load 1KΩ, Max. voltage supply 24V)

| Range | Resolution | Accuracy |
|---------|------------|----------------|
| 0~4mA | 1μA | ± 0.025% ±10μA |
| 4~20mA | 1μA | ± 0.025% ±5μA |
| 20~24mA | 1μA | ± 0.025% ±5μA |

When output Open, the LCD displays "OL".

DC V SOURCE (Max. load 24mA, Short circuit protection < 25mA)

| Range | Resolution | Accuracy |
|--------|------------|----------------|
| 0~4V | 1mV | ± 0.05% ± 10mV |
| 4~20V | 1mV | ± 0.05% ±5mV |
| 20~24V | 1mV | ± 0.05% ±5mV |

When output Short circuit, the LCD displays "OL".

Frequency SOURCE (TTL, Square wave, Duty cycle = 1~99%)

| Range (Hz) | Resolution | Accuracy |
|---------------|------------|----------|
| 1.0~1000.0Hz | 0.1Hz | 0.1Hz |
| 1000~10000Hz | 1Hz | 1Hz |
| 10000~20000Hz | 1Hz | 10Hz |

DC mA MEASURE

| Range | Resolution | Accuracy |
|-----------|------------|--------------|
| 0.005~4mA | 1uA | ±0.025%±5dgt |
| 4~20mA | 1uA | ±0.025%±5dgt |
| 20~24mA | 1uA | ±0.025%±5dgt |

If reading of mA (measure) is less than 5 digits, it is displayed as 0.

DC V MEASURE

| Range | Resolution | Accuracy |
|-------|------------|--------------|
| 0~24V | 0.001V | ±0.025%±5dgt |

If reading of V (measure) is less than 5 digits, it is displayed as 0.

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR

Temperature of Thermocouples (MEASURE)

(Resolution 0.1°C&0.1°F, Internal cold junction compensation, Thermocouples accuracy not included, 3 minutes after plugging in thermocouples.)

| | °C | | °F | |
|---|--------------|----------|--------------|----------|
| | Range | Accuracy | Range | Accuracy |
| K | -200 to -150 | 2.0 | -382 to -238 | 3.6 |
| | -150 to 0 | 1.2 | -238 to 32 | 2.1 |
| | 0 to 1000 | 0.8 | 32 to 1832 | 1.4 |
| | 1000 to 1370 | 1.2 | 1832 to 2498 | 2.1 |
| J | -200 to -150 | 2.0 | -382 to -238 | 3.6 |
| | -150 to 0 | 1.0 | -238 to 32 | 1.8 |
| | 0 to 1050 | 0.7 | 32 to 1922 | 1.2 |
| E | -200 to -150 | 1.5 | -382 to -238 | 2.7 |
| | -150 to 0 | 0.9 | -238 to 32 | 1.6 |
| | 0 to 850 | 0.7 | 32 to 1562 | 1.2 |
| T | -200 to -150 | 1.5 | -382 to -238 | 2.7 |
| | -150 to 0 | 1.2 | -238 to 32 | 2.1 |
| | 0 to 400 | 0.8 | 32 to 752 | 1.4 |
| R | 0 to 500 | 1.8 | 32 to 932 | 3.2 |
| | 500 to 1760 | 1.5 | 932 to 3200 | 2.7 |
| S | 0 to 500 | 1.8 | 32 to 932 | 3.2 |
| | 500 to 1760 | 1.5 | 932 to 3200 | 2.7 |
| N | -200 to 0 | 1.5 | -328 to 32 | 2.7 |
| | 0 to 1300 | 0.9 | 32 to 2372 | 1.6 |
| L | -200 to 0 | 0.9 | -328 to 32 | 1.6 |
| | 0 to 900 | 0.7 | 32 to 1652 | 1.2 |
| U | -200 to 0 | 1.1 | -328 to 32 | 1.9 |
| | 0 to 600 | 0.7 | 32 to 1112 | 1.2 |
| B | 600 to 800 | 2.2 | 1112 to 1472 | 3.9 |
| | 800 to 1000 | 1.8 | 1472 to 1832 | 3.2 |
| | 1000 to 1820 | 1.4 | 1832 to 3308 | 2.5 |
| C | 0 to 1800 | 1.0 | 32 to 3272 | 1.8 |
| | 1800 to 2310 | 1.5 | 3272 to 4190 | 2.7 |

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR



General Specifications:

| | |
|-----------------------|---|
| Dimension | 214.0 (L) x 98.7(W) x 56.0(H) mm 8.4" (L) x 3.9" (W) x 2.2" (H) |
| Weight | 650g / 22.9oz (batteries included) |
| Operation Environment | 0°C ~ 50°C < 85% RH |
| Storage Environment | -20°C ~ 60°C < 75% RH |
| Accessories | Carrying case x 1 User manual x 1 1.5V SUM-3 Battery x 5 K-type thermocouples (1M, single plug) x 1 Alligator clips x 2 (black and red) Test leads x 2 (black and red) |

PROVA INSTRUMENTS INC.

Add: 6F-2, No. 129, Lane 235, Pao-Chiao Road, Shin-Tien District,
New Taipei City 23145, TAIWAN

Tel: 886-2-89191255


Fax: 886-2-89191489

E-mail: prova@ms3.hinet.net

Website: www.prova.com.tw

 +982165565901

 +982144584619

 +989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR