


HDS Series 1-channel Handheld Digital Storage Oscilloscope



- + 2 in 1 (DSO + Multimeter)
- + Auto-scale function
- + FFT function
- + 20 group automatic measurement options
- + Bandwidth : 20MHz - 100MHz
- + USB data transmission supported
- + Rechargeable Li-ion battery (6 hours' backup)
- + Waveform record and replay
- + Multimeter newly supported SCPI



+ Multimeter Specifications

Full Scale Reading	3 $\frac{3}{4}$ digits (max 4000 count)	Diode	0V - 1.5V
Input Impedance	10 M Ω	On / Off Test	<50 (\pm 30) beeping
Voltage	VDC : 400mV, 4V, 40V, 400V, 1000V : \pm (1% \pm 1 digit); max input : DC 1000V VAC : 4V, 40V, 400V : \pm (1% \pm 3 digits), 750V : \pm (2% \pm 3 digits); Frequency : 40Hz - 400Hz; max input : AC 750V (virtual value)		
Current	DC : 40mA, 400mA : \pm (1.5% \pm 1 digit), 10A : \pm (3% \pm 3 digits) AC : 40mA : \pm (1.5% \pm 3 digits), 400mA : \pm (2% \pm 1 digit), 10A : \pm (5% \pm 3 digits)		
Impedance	400 Ω : \pm (1% \pm 3 digits), 40K Ω - 4M Ω : \pm (1% \pm 1 digit), 40M Ω : \pm (1.5% \pm 3 digits)		
Capacitance	51.2nF - 100uF : \pm (3% \pm 3 digits)		

Specifications subject to change without prior notice.

+ Performance Specifications

Model	HDS1021M-N	HDS2061M-N	HDS3101M-N
Bandwidth	20MHz	60MHz	100MHz
Sample Rate	500MS/s	500MS/s	1GS/s
Horizontal Scale (s/div)	5ns/div - 100s/div, step by 1 - 2.5 - 5	5ns/div - 100s/div, step by 1 - 2 - 5	
Rise Time (at input, typical)	\leq 17.5ns	\leq 5.8ns	\leq 3.5ns
Display	3.7" color TFT display (640 x 480 pixels)		
Channel	single		
Input Impedance	1M Ω \pm 2%, in parallel with 18pF \pm 5pF	1M Ω \pm 2%, in parallel with 15pF \pm 5pF	
Record Length	6K points		
Interpolation	sin(x)/x		
Probe Attenuation Factor	1X, 10X, 100X, 1000X		
Input Coupling	DC, AC, and GND		
DC Accuracy (average)	average $>$ 16 : \pm (5% reading + 0.05 div) for Δ V		
Vertical Sensitivity	5mV/div - 5V/div (at input)		
Vertical Resolution (A/D)	8 bits		
Max Input Voltage	400V (DC + AC peak, 1M Ω input impedance, probe attenuation 10 : 1), CAT II		
Trigger Type	Edge, and Video		
Trigger Mode	Auto, Normal, and Single		
Trigger Level	\pm 6 divisions from screen center		
Acquisition Mode	Sample, Peak Detect, and Average		
DC Gain Accuracy	\pm 3%		
Automatic Measurement	Vpp, Vavg, Vrms, Freq, Period, Vmax, Vmin, Vtop, Vbase, Vamp, Overshoot, Preshoot, Rise Time, Fall Time, Delay A \rightarrow B \downarrow , Delay A \rightarrow B \uparrow , +Width, -Width, +Duty, -Duty		
Waveform Storage	4 waveforms		
Communication Interface	mini-USB, mini-RS232		
Power Supply	100V-240V AC, 50/60Hz		
Li-ion Battery	7.4V, 6 hours' operation		
Dimensions (W x H x D)	115 x 180 x 40 (mm)		
Device Weight	645.00 g		

+ Application

electronic circuit debugging education and training circuit testing automobile maintenance and testing design and manufacture

+ Accessories

The accessories subject to final delivery.



+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR