

Performance Specifications


Model	RDS1021	RDS1021I
Bandwidth	25MHz	
Sample Rate	100MS/s	
Horizontal Scale (s/div)	5ns/div - 100s/div, step by 1 - 2 - 5	
Rise Time	≤14ns	
Record Length	5K	
Input Coupling	DC, AC, and GND	
Input Impedance	10MΩ±2%(X10), 1MΩ±2%(X1)	
Input Capacitance	20pF±5pF	
Max Input Voltage	50V (PK - PK) (DC + AC, PK - PK)	400V (PK - PK) (DC + AC, PK - PK)
DC Gain Accuracy	±3%	
DC Accuracy (average)	average≥16 : ±(3% reading + 0.05 div) for ΔV	
Analog Bandwidth	25MHz	
Probe Attenuation Factor	1X, 10X	
LF Respond (AC,-3dB)	≥10Hz	
Interpolation	sin(x)/x	
Displacement	±10div	
Interval (ΔT) Accuracy (full bandwidth)	Single : ±(1 interval time + 100ppm × reading + 0.6ns), Average>16 : ±(1 interval time + 100ppm × reading + 0.4ns)	
Vertical Resolution (A/D)	8 bits	
Vertical Sensitivity	5mV/div - 5V/div	

Performance Specifications

Model	RDS1021	RDS1021I
Trigger Type	Edge, Pulse, Slope	
Trigger Mode	Auto, Normal, Single	
Trigger Level	±5 divisions from screen center	
Acquisition Mode	Sample, Peak Detect and Average	
Cursor Measurement	ΔV and ΔT between cursors	
Automatic Measurement	Vpp, Vavg, Vrms, Freq, Period, Vmax, Vmin, Vtop, Vbase, Overshoot, Preshoot, Rise Time, Fall Time, +Width, -Width, +Duty, -Duty	
Waveform Math	FFT	
Communication Interface	USB2.0	
Dimension (W×H×D)	150 × 20 × 18 (mm)	
Weight (without package)	0.27 kg	

Specifications subject to change without prior notice.

The accessories subject to final delivery.



Grounding Clamp

Protection Cover

USB Cable

Manual

CD Rom

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR