

## FILM VIEWER DF-2C15

This viewer is designed suitably for such requirements since minute defect view ability is required when viewing a film. It is also designed for allowing a film with high density with a spot viewer adhered. Working efficiency of a worker is improved with a foot switch adhered.



Illumination control device on fluorescent lamp helps operator to read films very easily DF-2C15 adopts electronic ballast for SWITCHING with high frequency. It would be effective to protect operator's eye against high luminance and flickering of lamp. A halogen lamp has a good advantage for reading POINT defects. The cooling fan is effective to reduce the heat and allows long working time Built-in mirror plate is helpful to raise illumination more effectively. By using Foot S/W operator could save working time for reading

### 사양 / SPECIFICATION

Power source	AC220V / 50/60Hz / 2,5A AC110V / 50/60Hz / 4,5A
Material	ALUMINUM 2T
Lamp	(Fluorescent Lamp) 15W X 2EA, (Halogen Lamp) 500W X 1EA
Cooling Fan	AC 230V 50/60Hz 9/7W
Dimension	640(L) X 195(W) X 195(H)mm
Illuminance	20V 50/60Hz - (Fluorescent Lamp) 20,000Lux , (Halogen Lamp) 200,000Lux 110V 50/60Hz - (Fluorescent Lamp) 18,000Lux , (Halogen Lamp) 130,000Lux
Weight	220V 50/60Hz 7kg 110V 50/60Hz 8kg
Viewing Mask	3 1/2 X 12" , 4 1/2 X 12"
Power cable	2m(0,75SQ X 3c), FOOT S/W cable : 2m

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR