



# THE PalmScope™

FGJ

FARHAN GOSTAR JOONOB

## Specifications:

**Probe Length:** 24 in. (0.6m)

**Camera Head Diameter:** 0.35 in. (9mm)

**Probe Water/Dust/Oil Resistance:** to IP67 standard

**LCD Size:** 2.7 in. (68.5mm) diagonal

**LCD/Camera Resolution:** 320 x 240 pixels (QVGA)

**Camera Depth of Field:** 1 in. to 10 ft. (25mm to 3m)

**Camera Field of View:** 60°

**Screen Controls:** Brightness up and down, 1 to 4X zoom, 180° flip

**Case Impact Resistance:**

From height of 39 in. (1m) onto 2 in. (50mm) thick hardwood

**Dimensions:** 5.4 x 2.9 x 1.5 in. (136 x 73 x 39mm)

**Weight:** 9 oz. (250g)

**Power Source:** 4 "AAA" batteries (not included)

## Includes:

Nylon Pouch with Belt Clip, Four Probe Tip Accessories (pickup hook, magnetic pickup, 90° mirror, thread protector), User's Manual, 1 Year Limited Warranty



**CALRIGHT INSTRUMENTS**  
The Right Source For Your Test & Measurement Needs

8715 Mesa Point Terrace San Diego, CA 92154  
Toll Free: 1.866.363.6634 Tel: 1.619.429.4545 Fax: 1.619.374.7012  
Email: sales@calright.com <http://www.calright.com>

No. DCS950 (actual size)



Perfect for crowded modern engine compartments



Look behind a wall through any small hole



Handy pouch with belt clip



Probe Tips



General Tools & Instruments

80 White Street, New York, NY 10013-3567

TEL: 212. 431. 6100 TOLL FREE: 800. 697. 8665

sales@generaltools.com www.generaltools.com

DCS950SS Printed in USA 01/14



+982165565901



+982144584619



+989034119385



Tehran, Tehransar

پتروفرفهان گستر جنوب

DIGINDT.IR

FGJ-NDT.IR