

VANTA

Rugged. Revolutionary. Productive.



پتروفرهان گستر جنوب

DIGINDT.IR

FGJ-NDT.IR

Vanta™ handheld XRF analyzers are rugged and built for analytically demanding applications in the harshest environments. Vanta analyzers are IP 65* rated for protection against dust and water, are drop tested, and built to withstand a temperature range of -10 °C to 50 °C (14 °F to 122 °F).**

Vanta analyzers provide fast, accurate elemental analysis. Each device features Olympus' new Axon™ technology, a revolution in XRF signal processing that provides accurate, repeatable results for greater productivity and a fast return on investment. Vanta analyzers feature an intuitive interface and application-specific software so new users can work with the device with minimal training. Data is easily exported via Wi-Fi, Bluetooth®, or USB.

The Vanta Series

No matter the model, each Vanta analyzer is engineered for durability and analytical superiority. Olympus manufactures Vanta™ analyzers to suit a variety of applications depending on your needs.

M Series

Our most powerful Vanta analyzers feature exceptional performance to handle the most demanding applications. Each M Series analyzer comes equipped a large-area silicon drift detector, your choice of either a rhodium (Rh) or a tungsten (W) anode, and a 50 kV X-ray tube.

C Series

The C Series combine value with superior speed, limits of detection (LODs), and elemental range. Each C Series analyzer is equipped with a silicon drift detector and your choice of an Rh or W anode 40 kV X-ray tube, or a silver (Ag) anode at 50 kV X-ray tube.

VANTA Specifications

Dimensions (W × H × D)	8.3 cm × 28.9 cm × 24.2 cm (3.25 in. × 11.4 in. × 9.5 in.)
Weight	1.70 kg (3.75 lb) with battery, 1.48 kg (3.25 lb) without battery
Excitation Source	4-Watt X-ray tube with application optimized anode material (rhodium (Rh), silver (Ag), or tungsten (W)) M Series (Rh & W) and C Series (Ag): 8–50 kV C Series (Rh & W): 8–40 kV
Primary Beam Filtration	8-position auto selected filter per beam per mode
Detector	M Series: Large area Silicon Drift Detector C Series: Silicon Drift Detector
Power	Removable 14.4 V Li-Ion battery or 18 V power transformer 100-240 VAC, 50–60 Hz, 70 W max
Display	800 × 480 (WVGA) LCD with capacitive touch-screen supporting gesture control
Operating Environment	Temperature: -10 °C to 50 °C (continuous duty cycle with optional fan) Humidity: 10% to 90% relative humidity non-condensing
Drop Test	Military Standard 810-G 4-foot (1.3 M) drop test
IP Rating	M Series IP 64: dust tight and protected against water splashing from all directions C Series IP 65: dust tight and protected against water jets from all directions
Pressure Correction	Built-in barometer for automatic altitude and air density correction
GPS	Embedded GPS / GLONASS receiver
Operating System	Linux
Data Storage	4 GB embedded storage, micro SD slot for expandable storage
USB	(2) USB 2.0 type A host ports for accessories such as Wi-Fi, Bluetooth®, and USB flash drives. (1) USB 2.0 type mini-B port for connection to computer.
WiFi	Supports 802.11 b/g/n (2.4 GHz) via optional USB adapter
Bluetooth	Supports Bluetooth and Bluetooth Low-Energy via optional USB adapter
Aiming Camera	Full VGA CMOS camera
Panoramic Camera	5-megapixel CMOS camera with autofocus lens

www.olympus-ims.com

OLYMPUS®

For enquiries - contact
www.olympus-ims.com/contact-us

OLYMPUS CORPORATION OF THE AMERICAS
48 Woerd Avenue, Waltham, MA 02453, USA, Tel.: (1) 781-419-3900
12569 Gulf Freeway, Houston, TX 77034, USA, Tel.: (1) 281-922-9300

OLYMPUS SCIENTIFIC SOLUTIONS AMERICAS
is certified to ISO 9001, ISO 14001, and OHSAS 18001.

*M Series analyzers are IP 64 rated.
** With optional fan. The fan assembly is IP 54 rated. Operates continuously at 33 °C without the fan.
All specifications are subject to change without notice.
All brands are trademarks or registered trademarks of their respective owners and third party entities.
The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Olympus Corporation is under license.
Copyright © 2016 by Olympus.



Vanta for Regulatory and Safety Screening

VANTA

Rugged. Revolutionary. Productive.



Applications

Consumer Product Compliance

With Vanta™ analyzers, manufacturers and recyclers can screen for Pb, Cd, As, Hg, Cr, and Br, along with other toxic metals in consumer products for compliance with RoHS requirements including:

- Toys, jewelry, trinkets, crayons, chalk, plastics, lunch boxes, and backpacks
- Apparel and accessories: clothing, zippers, buttons, applique, rhinestones, trim, bags, and wallets
- Sporting goods, swing sets, picnic tables, decks, and fences
- Decorative food ware, colored ceramics, and silver-plated hollowware
- Candy wrappings, baby food, supplements, and foodstuff
- Drapery, furnishings, and rugs
- Cars, car seats, leather, fiber, trim, knobs, wheels, and mats
- Lead in a water tap or pipeline
- Heavy metals in cosmetics

Recycled Products and Consumer Electronics

Vanta analyzers can be configured to provide pass/fail results for a variety of recycled products and consumer electronics including:

- RoHS (Restriction of Hazardous Substances Directive) Compliance—Pb, Hg, Cr, Br, and Cd
- Lead-free compliance in boards, cables, connectors, PCBs, metal components, and solders
- Packaging material
- Batteries, paint, fertilizers, plastics, and metal coatings
- Cars, car seats, leather, fiber, trim, knobs, wheels, and mats
- Wood, paper, and cardboard
- Halogen free

Compliance with Global Hazardous Substance Regulations and Testing Methods

Vanta analyzers are accepted as a screening tool when testing for compliance with the following global hazardous substance regulations and testing methods:

- EU RoHS Directive (2011/65/EU)
- China RoHS Directive (ACPEIP)
- Japan RoHS
- Korean RoHS Directive
- USA CPSIA (HR4040)
- USA Halogen Free Directive
- California Proposition 65
- USA CPSC-CH-E1002-08 SOP
- IEC 62321



Fast, Reliable Results when Safety is Paramount



Rugged

Working conditions can be tough on electronic devices, often causing breakdowns that cost time and money. Vanta analyzers are durable for increased uptime and a lower cost of ownership. Vanta analyzers are IP65* rated to withstand rain, dirt, and dust and are drop tested to U.S. Department of Defense standards (MIL-STD-810G) to help prevent breakages and costly repairs. The detector shutter on silicon drift detector models helps prevent punctures so you can analyze rough surfaces with confidence.

Able to withstand a temperature range of -10 °C to 50 °C (14 °F to 122 °F), Vanta analyzers help you get 100% testing time, even in hot environments.** Their ruggedness and durability make Vanta analyzers resistant to damage for maximum productivity and uptime with minimal cost of ownership.



Productive

Vanta analyzers include innovative software features that enable users to utilize results immediately and perform real-time reporting. Test times take as little as 1 to 2 seconds with even greater accuracy and precision. The user interface is intuitive and customizable so that operators can begin using the device with minimal training. Vanta analyzers maximize user throughput and make workflow management and data archiving easy.

- A new, intuitive interface enables the user to quickly navigate the device's settings and software functions.
- The UI can be configured based on a customer's specific needs. Users can customize which software features and functions are displayed on the main screen.
- Data are easily exported via a USB flash drive, wireless LAN (Wi-Fi), or Bluetooth®. Vanta analyzers are designed to enable powerful cloud applications.
- Vanta analyzers feature a clear, bright LCD touch screen that is readable in any light.
- Unique username and password login for each user.
- Ergonomic buttons and an industrial-grade, push-button joystick enable users to easily navigate the system with gloved hands.



Revolutionary

Every circuit, contour, and interface of Vanta handhelds is engineered to be the best of its kind. Vanta analyzers incorporate Olympus' Axon™ technology, a breakthrough in XRF signal processing that delivers accurate and repeatable test data and enables inspectors to get pass/fail screening results in seconds. Axon™ technology uses ultra-low-noise electronics that facilitate higher X-ray counts per second and faster results.

Coupled with a new quad-core processor, Axon technology makes Vanta analyzers remarkably responsive, pushing the limits of performance so you get the best results in the least amount of time. Axon technology provides test-to-test and instrument-to-instrument repeatability. Whether it's your first test on your first analyzer or your thousandth test with your hundredth analyzer, the Vanta handheld XRF gives you the same result every time.

پتروفرفرہان گستر جنوب

DIGINDT.IR

FGJ-NDT.IR

The Vanta Series

No matter the model, the rugged, fast, and reliable Vanta™ analyzer features Olympus' Axon™ technology and is rated to pass a 4-foot drop test. C Series models are IP65 rated and M Series models are IP64 rated.



M Series

Our most powerful Vanta analyzers feature exceptional performance to handle the most demanding applications. Each M Series analyzer comes equipped with a large-area silicon drift detector, either a tungsten (W) or rhodium (Rh) anode, and a 50 kV X-ray tube.

C Series

The C Series combine value with superior speed, limits of detection (LODs), and elemental range. Each C Series analyzer is equipped with a silicon drift detector and a Rhodium (Rh) or Tungsten (W) anode 40 kV X-ray tube, or a silver (Ag) anode 50 kV X-ray tube.

Olympus

Olympus is a leader in XRF technology with a reputation for quality and accuracy. We are committed to providing the best technical support and after-sales service for our products, applications, training, and technologies through our global network of sales and customer service teams.

+982165565901

+982144584619

+989034119385

Tehran, Tehransar

پتروفرهان گستر جنوب

DIGINDT.IR

FGJ-NDT.IR

www.olympus-ims.com

OLYMPUS

OLYMPUS CORPORATION OF THE AMERICAS
48 Woerd Avenue, Waltham, MA 02453, USA, Tel.: (1) 781-419-3900
110 Magellan Circle, Webster TX, 77598, USA, Tel.: (1) 281-922-9300

For inquiries - contact
www.olympus-ims.com/contact-us

OLYMPUS SCIENTIFIC SOLUTIONS AMERICAS CORP.
is certified to ISO 9001, ISO 14001, and OHSAS 18001.

*M Series analyzers are IP 64 rated

** With optional fan. The fan assembly is IP56 rated. Operates continuously at 33 °C without the fan.
All specifications are subject to change without notice.
All brands are trademarks or registered trademarks of their respective owners and third party entities.
Vanta and Axon are trademarks of Olympus Corporation. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Olympus Corporation is under license.
Copyright © 2017 by Olympus.



PHOTON ENERGIES, IN ELECTRON VOLTS, OF PRINCIPAL K- AND L-SHELL EMISSIONLINES

Element	Symbol	Atomic #	K _{α1}	K _{β1}	L _{α1}	L _{β1}
Actinium	Ac	89	90.88	102.85	12.65	15.71
Aluminum	Al	13	1.49	1.56	0	0
Antimony	Sb	51	26.36	29.73	3.6	3.84
Argon	Ar	18	2.96	3.19	0	0
Arsenic	As	33	10.54	11.73	1.28	1.32
Astatine	At	85	81.52	92.3	11.43	13.88
Barium	Ba	56	32.19	36.38	4.47	4.83
Beryllium	Be	4	0.11	0	0	0
Bismuth	Bi	83	77.11	87.34	10.84	13.02
Boron	B	5	0.18	0	0	0
Bromine	Br	35	11.92	13.29	1.48	1.53
Cadmium	Cd	48	23.17	26.1	3.13	3.32
Calcium	Ca	20	3.69	4.01	0.34	0.34
Carbon	C	6	0.28	0	0	0
Cerium	Ce	58	34.72	39.26	4.84	5.26
Cesium	Cs	55	30.97	34.99	4.29	4.62
Chlorine	Cl	17	2.62	2.82	0	0
Chromium	Cr	24	5.41	5.95	0.57	0.58
Cobalt	Co	27	6.93	7.65	0.78	0.79
Copper	Cu	29	8.05	8.91	0.93	0.95
Dysprosium	Dy	66	46	52.12	6.5	7.25
Erbium	Er	68	49.13	55.68	6.95	7.81
Europium	Eu	63	41.54	47.04	5.85	6.46
Fluorine	F	9	0.68	0	0	0
Francium	Fr	87	86.1	97.47	12.03	14.77
Gadolinium	Gd	64	43	48.7	6.06	6.71
Gallium	Ga	31	9.25	10.26	1.1	1.12
Germanium	Ge	32	9.89	10.98	1.19	1.22
Gold	Au	79	68.8	77.98	9.71	11.44
Hafnium	Hf	72	55.79	63.23	7.9	9.02
Holmium	Ho	67	47.55	53.88	6.72	7.53
Indium	In	49	24.21	27.28	3.29	3.49
Iodine	I	53	28.61	32.29	3.94	4.22
Iridium	Ir	77	64.9	73.56	9.18	10.71
Iron	Fe	26	6.4	7.06	0.71	0.72
Krypton	Kr	36	12.65	14.11	1.59	1.64
Lanthanum	La	57	33.44	37.8	4.65	5.04
Lead	Pb	82	74.97	84.94	10.55	12.61
Lithium	Li	3	0.05	0	0	0
Lutetium	Lu	71	54.07	61.28	7.66	8.71
Magnesium	Mg	12	1.25	1.3	0	0
Manganese	Mn	25	5.9	6.49	0.64	0.65
Mercury	Hg	80	70.82	80.25	9.99	11.82
Molybdenum	Mo	42	17.48	19.61	2.29	2.39
Neodymium	Nd	60	37.36	42.27	5.23	5.72

Element	Symbol	Atomic #	K _{α1}	K _{β1}	L _{α1}	L _{β1}
Neon	Ne	10	0.85	0	0	0
Nickel	Ni	28	7.48	8.26	0.85	0.87
Niobium	Nb	41	16.62	18.62	2.17	2.26
Nitrogen	N	7	0.39	0	0	0
Osmium	Os	76	63	71.41	8.91	10.36
Oxygen	O	8	0.52	0	0	0
Palladium	Pd	46	21.18	23.82	2.84	2.99
Phosphorus	P	15	2.01	2.14	0	0
Platinum	Pt	78	66.83	75.75	9.44	11.07
Polonium	Po	84	79.29	89.8	11.13	13.45
Potassium	K	19	3.31	3.59	0	0
Praseodymium	Pr	59	36.03	40.75	5.03	5.49
Promethium	Pm	61	38.72	43.83	5.43	5.96
Protactinium	Pa	91	95.87	108.43	13.29	16.7
Radium	Ra	88	88.47	100.13	12.34	15.24
Radon	Rn	86	83.78	94.87	11.73	14.32
Rhenium	Re	75	61.14	69.31	8.65	10.01
Rhodium	Rh	45	20.22	22.72	2.7	2.83
Rubidium	Rb	37	13.4	14.96	1.69	1.75
Ruthenium	Ru	44	19.28	21.66	2.56	2.68
Samarium	Sm	62	40.12	45.41	5.64	6.21
Scandium	Sc	21	4.09	4.46	0.4	0.4
Selenium	Se	34	11.22	12.5	1.38	1.42
Silicon	Si	14	1.74	1.84	0	0
Silver	Ag	47	22.16	24.94	2.98	3.15
Sodium	Na	11	1.04	1.07	0	0
Strontium	Sr	38	14.17	15.84	1.81	1.87
Sulfur	S	16	2.31	2.46	0	0
Tantalum	Ta	73	57.53	65.22	8.15	9.34
Technetium	Tc	43	18.37	20.62	2.42	2.54
Tellurium	Te	52	27.47	31	3.77	4.03
Terbium	Tb	65	44.48	50.38	6.27	6.98
Thallium	Tl	81	72.87	82.58	10.27	12.21
Thorium	Th	90	93.35	105.61	12.97	16.2
Thulium	Tm	69	50.74	57.52	7.18	8.1
Tin	Sn	50	25.27	28.49	3.44	3.66
Titanium	Ti	22	4.51	4.93	0.45	0.46
Tungsten	W	74	59.32	67.24	8.4	9.67
Uranium	U	92	98.44	111.3	13.61	17.22
Vanadium	V	23	4.95	5.43	0.51	0.52
Xenon	Xe	54	29.78	33.62	4.11	4.42
Ytterbium	Yb	70	52.39	59.37	7.42	8.4
Yttrium	Y	39	14.96	16.74	1.92	2
Zinc	Zn	30	8.64	9.57	1.01	1.03
Zirconium	Zr	40	15.78	17.67	2.04	2.12