

INFRARED THERMOMETERS

MS6540A/MS6540B

NON-CONTACT INFRARED THERMOMETERS

EMC

MASTECH®



MS6540A



MS6540B

Specifications

	MS6540A	MS6540B
Temperature Range	-32°C~850°C -25°F~1562°F	-32°C~1050°C -25°F~1922°F
Temperature Accuracy	>510°C ±1.5% 50°C~510°C ±(1.5%+1°C) 15°C~50°C ±(1.5%+2°C) -32°C~15°C ±3°C	>510°C ±1.5% 50°C~510°C ±(1.5%+1°C) 15°C~50°C ±(1.5%+2°C) -32°C~15°C ±3°C
Temperature Resolution	±0.1°C/±0.1°F	±0.1°C/±0.1°F
Repeatability	±0.5°C or ±0.5%	±0.5°C or ±0.5%
Distance to Spot (D : S)	30:1	30:1
°C/°F Selection	✓	✓
Emissivity	Digitally Adjustable from 0.10 to 1.00 by 0.01	
Response Time	500ms	500ms
Laser Target Pointer	✓	✓
Data Logging	100 groups	100 groups
Reading Hold	✓	✓
MAX, MIN, DIF, AVG	✓	✓
Temperature Alarm Setting	✓	✓
Display Backlight	✓	✓
Low Battery Display	✓	✓
General Characteristic		
Power Supply	1×9V 6F22 Battery	1×9V 6F22 Battery
Product Size	140mm×56mm×190mm/ 5.5"×2.2"×7.5"	140mm×56mm×190mm/ 5.5"×2.2"×7.5"
Product Weight	500g/1.1lb	500g/1.1lb
Certificate	CE	CE

پتروفرهان گستر جنوب



+982165565901

FGJ-NDT.IR



+982144584619

DIGINDT.IR



+989034119385