



پتروفرهان گستر جنوب

Tehran, Tehransar



UNI-T®

VIII. Technical indexes

Function	UT330A	UT330B	UT330C			
Water and dust resistance	IP67	IP67	IP67			
Measurement range	Temperature: -40°C ~80°C	Temperature: -40°C ~80°C	Temperature: -40°C ~80°C			
		Humidity: 0%RH~100%RH, non-condensation	Humidity: 0%RH~100%RH, non-condensation			
Resolution	Temperature 0.1°C	Temperature 0.1°C	Temperature 0.1°C			
		Humidity: 0.1%RH	Humidity: 0.1%RH			
		Atmospheric pressure: 0.1hPa	Atmospheric pressure: 0.1hPa			
Measurement accuracy	Temperature: -40°C~-30°C: ±2.0°C -30°C~0°C: ±1.0°C 0°C~40°C: ±0.5°C 40°C~70°C: ±1.0°C 70°C~80°C: ±2.0°C	Temperature: -40°C~-30°C: ±2.0°C -30°C~0°C: ±1.0°C 0°C~40°C: ±0.5°C 40°C~70°C: ±1.0°C 70°C~80°C: ±2.0°C Humidity (@25°C): ±3.0% RH (20% RH~80%RH) ±5.0%RH (<20%RH or >80%RH)	Temperature: -40°C~-30°C: ±2.0°C -30°C~0°C: ±1.0°C 0°C~40°C: ±0.5°C 40°C~70°C: ±1.0°C 70°C~80°C: ±2.0°C Humidity (@25°C): ±3.0% RH (20% RH~80%RH) ±5.0%RH (<20%RH or >80%RH) Atmospheric pressure (@25): ±3 hPa			
				Data storage	0 ~ 60000	0 ~ 60000

UNI-T®

UNI-TREND TECHNOLOGY (CHINA) CO., LTD.

No6, Gong Ye Bei 1st Road,
Songshan Lake National High-Tech Industrial
Development Zone, Dongguan City,
Guangdong Province, China
Tel: (86-769) 8572 3888
http://www.uni-trend.com

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR