



پترو فرهان گستر جنوب

Tehran, Tehransar



- **Laser Class:** Class 2 (IEC/EN60825-1/2014),  $\leq 1\text{mW}$  power output
- **Laser Wavelength:** 510-520nm
- **Number of Lines & Range:** 12 lines,  $3 \times 360^\circ$
- **Horizontal/Vertical Accuracy:**  $\pm 3\text{mm}$  at 10m.
- **Leveling/Compensation Range:**  $\pm 4^\circ$
- **Leveling time, typical:**  $\leq 3\text{ s}$
- **IP Rating:** IP65 water/debris resistance and shockproof, reliable, and tough
- **Power Source:** 7.4V / 2600mAh Li-ion Battery & 4×"AA" (LR6) batteries
- **Working Distance (Line):** 25m, With Firecore Laser Receiver extend to 50m ( with Firecore Receiver FD20:B07VKR7YQT )
- **Operating Time with Lithium Battery:** 2X10 hours with all laser beams on
- **Mount Size:** 1/4"-20
- **Operation Temperature Range:** Between  $-10^\circ\text{C}$  and  $+40^\circ\text{C}$
- **Storage Temperature Range:** Between  $-20^\circ\text{C}$  and  $+60^\circ\text{C}$

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR