

# DISSOLVED OXYGEN TRANSMITTER

Model : TR-DOT1A4

*ISO-9001, CE, IEC1010*



**LUTRON ELECTRONIC**

*The Art of Measurement*



# DISSOLVED OXYGEN TRANSMITTER

Model : TR-DOT1A4

<b>Measure Range</b>	<p>Range 1 : <math>O^2</math> CAL.</p> <p>Range 2 : DO : 0 -20 mg/L</p>
<b>Output</b>	<p>4 - 20 mA</p> <p>Range 1 ( CAL ) : 20.9 % <math>O^2</math> = 12 mA</p> <p>Range 2 ( DO ) : 0 mg/L = 4 mA 10 mg/L = 12 mA 20 mg/L = 20 mA</p>
<b>External Adjustment</b>	ZERO VR SPAN VR
<b>Power Supply</b>	90 - 260 ACV 50 Hz/60 Hz
<b>Operation Temperature</b>	0 - 50 °C 32 - 122 °F
<b>Operation Humidity</b>	Less than 80 %RH
<b>Accessory Included</b>	Dissolved Oxygen Probe Probe-filling electrolyte, OXEL-03 Spare diaphragms, OXDP-02
<b>Optional Accessories</b>	Probe-filling electrolyte, OXEL-03 Spare diaphragms, OXDP-02
<b>Mounting</b>	Din rail or Wall
<b>Case</b>	ABS plastic
<b>Others</b>	Separate probe with plug

\* Appearance and specifications listed in this brochure are subject to change without notice.

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR