

LOAD CELL TRANSMITTER

Model : TR-LDT1A4

ISO-9001, CE, IEC1010



(OPTIONAL)



Lutron

LUTRON ELECTRONIC

The Art of Measurement

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR



LOAD CELL TRANSMITTER

Model : TR-LDT1A4

Measure Range	Available for load cell 1 - 2 mV/V (Variable exciting voltage DC 4V-12V)
Output	4 - 20 mA 0 weight = 4 mA 1/2 weight = 12 mA F.S. weight = 20 mA
External Adjustment	ZERO VR SPAN VR
Power Supply	90 - 260 ACV 50 Hz/60 Hz
Operation Temperature	0 - 50 °C 32 - 122 °F
Operation Humidity	Less than 80 %RH
Accessory Included	Load cell is optional.
Optional Accessories	200 g load cell 2 Kg load cell 5 Kg load cell 100 Kg load cell 150 Kg load cell
Mounting Dimension	Din rail or Wall
Others	Four wires connection

* Appearance and specifications listed in this brochure are subject to change without notice.

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR